




PARTICLE SIZE DISTRIBUTION & CONSISTENCY LIMITS TEST REPORT

Client	Ports North	Job Number	107672522-5000
Client Address	Cnr Grafton and Hartley Streets, Cairns, Qld 4870	Date	16-Mar-12
Project	Dredge Material Assessment	Report Number	NQ-12105 Page No 1 of 1
Location	Cairns Shipping Channel	Sampling Method	As Supplied to Laboratory
Lab Ref No.	12/7067	Sample Identification	TP5 2.9-3.6m

Laboratory Specimen Description CH CLAY, high plasticity, pale grey and pale red brown, with trace of sand.
 (AS1726, App A, Sect 2)

PARTICLE SIZE DISTRIBUTION AS1289 3.6.1				CLASSIFICATION LIMITS AND MOISTURE CONTENT						
Sieve Size	% Passing	Spec. Lower	Spec. Upper	Test		Method	Result	Spec. Lower	Spec. Upper	
150 mm	100			Liquid Limit	%	AS1289 3.1.2	65			
100 mm	100			Plastic Limit	%	AS1289 3.2.1	18			
75 mm	100			Plasticity Index	%	AS1289 3.3.1	47			
53 mm	100			Linear Shrinkage	%	AS1289 3.4.1	ND			
37.5 mm	100			Moisture Content	%	AS1289 2.1.1	30.5			
26.5 mm	100			Sample History : Low Temp Oven Dried Preparation Method : Dry sieved Crumbling / Curling of Linear Shrinkage : - Linear Shrinkage Mould Length : - NP = non-plastic NO = not obtainable ND = not determined						
19.0 mm	100									
13.2 mm	100									
9.5 mm	100									
6.7 mm	100									
4.75 mm	100									
2.36 mm	100									
1.18 mm	100									
0.600mm	100									
0.425mm	100									
0.300mm	99									
0.150mm	94									
0.075mm	89									




	This document is issued in accordance with NATA's accreditation requirements.	 Darryl Murphy Laboratory Manager	20-Mar-12
	THIS DOCUMENT SHALL ONLY BE REPRODUCED IN FULL	AUTHORISED SIGNATORY	DATE



PARTICLE SIZE DISTRIBUTION & CONSISTENCY LIMITS TEST REPORT

Client	Ports North	Job Number	107672522-5000
Client Address	Cnr Grafton and Hartley Streets, Cairns, Qld 4870	Date	16-Mar-12
Project	Dredge Material Assessment	Report Number	NQ-12104
Location	Cairns Shipping Channel	Page No	1 of 1
Lab Ref No.	12/7066	Sampling Method	As Supplied to Laboratory
		Sample Identification	TP5 2.5-2.9m

Laboratory Specimen Description CH CLAY, high plasticity, grey, with trace of sand.
 (AS1726, App A, Sect 2)

PARTICLE SIZE DISTRIBUTION AS1289 3.6.1				CLASSIFICATION LIMITS AND MOISTURE CONTENT					
Sieve Size	% Passing	Spec. Lower	Spec. Upper	Test		Method	Result	Spec. Lower	Spec. Upper
150 mm	100			Liquid Limit	%	AS1289 3.1.2	59		
100 mm	100			Plastic Limit	%	AS1289 3.2.1	19		
75 mm	100			Plasticity Index	%	AS1289 3.3.1	40		
53 mm	100			Linear Shrinkage	%	AS1289 3.4.1	ND		
37.5 mm	100			Moisture Content	%	AS1289 2.1.1	76.4		
26.5 mm	100			Sample History : Low Temp Oven Dried Preparation Method : Dry sieved Crumbling / Curling of Linear Shrinkage : - Linear Shrinkage Mould Length : - NP = non-plastic NO = not obtainable ND = not determined					
19.0 mm	100								
13.2 mm	100								
9.5 mm	100								
6.7 mm	100								
4.75 mm	100								
2.36 mm	99								
1.18 mm	98								
0.600mm	98								
0.425mm	97								
0.300mm	97								
0.150mm	94								
0.075mm	88								



	This document is issued in accordance with NATA's accreditation requirements.	 Darryl Murphy Laboratory Manager	20-Mar-12
	THIS DOCUMENT SHALL ONLY BE REPRODUCED IN FULL	AUTHORISED SIGNATORY	DATE


PARTICLE SIZE DISTRIBUTION & CONSISTENCY LIMITS TEST REPORT



Client	Ports North	Job Number	107672522-5000
Client Address	Cnr Grafton and Hartley Streets, Cairns, Qld 4870	Date	16-Mar-12
Project	Dredge Material Assessment	Report Number	NQ-12103 Page No 1 of 1
Location	Cairns Shipping Channel	Sampling Method	As Supplied to Laboratory
Lab Ref No.	12/7065	Sample Identification	TP4 3.3-3.4m

Laboratory Specimen Description CH CLAY, high plasticity, dark grey.
 (AS1726, App A, Sect 2)

PARTICLE SIZE DISTRIBUTION AS1289 3.6.1				CLASSIFICATION LIMITS AND MOISTURE CONTENT						
Sieve Size	% Passing	Spec. Lower	Spec. Upper	Test		Method	Result	Spec. Lower	Spec. Upper	
150 mm	100			Liquid Limit	%	AS1289 3.1.2	68			
100 mm	100			Plastic Limit	%	AS1289 3.2.1	23			
75 mm	100			Plasticity Index	%	AS1289 3.3.1	45			
53 mm	100			Linear Shrinkage	%	AS1289 3.4.1	ND			
37.5 mm	100			Moisture Content	%	AS1289 2.1.1	106.6			
26.5 mm	100			Sample History : Low Temp Oven Dried Preparation Method : Dry sieved Crumbling / Curling of Linear Shrinkage : - Linear Shrinkage Mould Length : - NP = non-plastic NO = not obtainable ND = not determined						
19.0 mm	100									
13.2 mm	100									
9.5 mm	100									
6.7 mm	100									
4.75 mm	100									
2.36 mm	100									
1.18 mm	99									
0.600mm	98									
0.425mm	97									
0.300mm	97									
0.150mm	95									
0.075mm	93									

PARTICLE SIZE DISTRIBUTION




	This document is issued in accordance with NATA's accreditation requirements.	 Darryl Murphy Laboratory Manager	20-Mar-12
	THIS DOCUMENT SHALL ONLY BE REPRODUCED IN FULL	AUTHORISED SIGNATORY	DATE



PARTICLE SIZE DISTRIBUTION & CONSISTENCY LIMITS TEST REPORT

Client	Ports North	Job Number	107672522-5000
Client Address	Cnr Grafton and Hartley Streets, Cairns, Qld 4870	Date	16-Mar-12
Project	Dredge Material Assessment	Report Number	NQ-12102
Location	Cairns Shipping Channel	Page No	1 of 1
Lab Ref No.	12/7064	Sampling Method	As Supplied to Laboratory
		Sample Identification	TP3 2.8-3.2m

Laboratory Specimen Description CH CLAY, high plasticity, grey.
 (AS1726, App A, Sect 2)

PARTICLE SIZE DISTRIBUTION AS1289 3.6.1				CLASSIFICATION LIMITS AND MOISTURE CONTENT						
Sieve Size	% Passing	Spec. Lower	Spec. Upper	Test		Method	Result	Spec. Lower	Spec. Upper	
150 mm	100			Liquid Limit	%	AS1289 3.1.2	75			
100 mm	100			Plastic Limit	%	AS1289 3.2.1	22			
75 mm	100			Plasticity Index	%	AS1289 3.3.1	53			
53 mm	100			Linear Shrinkage	%	AS1289 3.4.1	ND			
37.5 mm	100			Moisture Content	%	AS1289 2.1.1	69.4			
26.5 mm	100			Sample History : Low Temp Oven Dried Preparation Method : Dry sieved Crumbling / Curling of Linear Shrinkage : - Linear Shrinkage Mould Length : - NP = non-plastic NO = not obtainable ND = not determined						
19.0 mm	100									
13.2 mm	100									
9.5 mm	100									
6.7 mm	100									
4.75 mm	100									
2.36 mm	100									
1.18 mm	100									
0.600mm	100									
0.425mm	100									
0.300mm	100									
0.150mm	100									
0.075mm	99									




	This document is issued in accordance with NATA's accreditation requirements.	 Darryl Murphy Laboratory Manager	20-Mar-12
	THIS DOCUMENT SHALL ONLY BE REPRODUCED IN FULL	AUTHORISED SIGNATORY	DATE



PARTICLE SIZE DISTRIBUTION & CONSISTENCY LIMITS TEST REPORT

Client	Ports North	Job Number	107672522-5000
Client Address	Cnr Grafton and Hartley Streets, Cairns, Qld 4870	Date	16-Mar-12
Project	Dredge Material Assessment	Report Number	NQ-12101
Location	Cairns Shipping Channel	Page No	1 of 1
Lab Ref No.	12/7063	Sampling Method	As Supplied to Laboratory
		Sample Identification	TP3 1.5-2.8m

Laboratory Specimen Description CH CLAY, high plasticity, grey.
 (AS1726, App A, Sect 2)

PARTICLE SIZE DISTRIBUTION AS1289 3.6.1				CLASSIFICATION LIMITS AND MOISTURE CONTENT						
Sieve Size	% Passing	Spec. Lower	Spec. Upper	Test		Method	Result	Spec. Lower	Spec. Upper	
150 mm	100			Liquid Limit	%	AS1289 3.1.2	73			
100 mm	100			Plastic Limit	%	AS1289 3.2.1	20			
75 mm	100			Plasticity Index	%	AS1289 3.3.1	53			
53 mm	100			Linear Shrinkage	%	AS1289 3.4.1	ND			
37.5 mm	100			Moisture Content	%	AS1289 2.1.1	67.5			
26.5 mm	100			Sample History : Low Temp Oven Dried Preparation Method : Dry sieved Crumbling / Curling of Linear Shrinkage : - Linear Shrinkage Mould Length : - NP = non-plastic NO = not obtainable ND = not determined						
19.0 mm	100									
13.2 mm	100									
9.5 mm	100									
6.7 mm	100									
4.75 mm	100									
2.36 mm	100									
1.18 mm	100									
0.600mm	100									
0.425mm	100									
0.300mm	99									
0.150mm	99									
0.075mm	98									




	This document is issued in accordance with NATA's accreditation requirements.	 Darryl Murphy Laboratory Manager	20-Mar-12
	THIS DOCUMENT SHALL ONLY BE REPRODUCED IN FULL	AUTHORISED SIGNATORY	DATE



PARTICLE SIZE DISTRIBUTION & CONSISTENCY LIMITS TEST REPORT

Client	Ports North	Job Number	107672522-5000
Client Address	Cnr Grafton and Hartley Streets, Cairns, Qld 4870	Date	16-Mar-12
Project	Dredge Material Assessment	Report Number	NQ-12100
Location	Cairns Shipping Channel	Page No	1 of 1
Lab Ref No.	12/7062	Sampling Method	As Supplied to Laboratory
		Sample Identification	TP2 1.6-1.7m

Laboratory Specimen Description CI CLAY, medium plasticity, pale grey, with trace of sand.
 (AS1726, App A, Sect 2)

PARTICLE SIZE DISTRIBUTION AS1289 3.6.1				CLASSIFICATION LIMITS AND MOISTURE CONTENT						
Sieve Size	% Passing	Spec. Lower	Spec. Upper	Test		Method	Result	Spec. Lower	Spec. Upper	
150 mm	100			Liquid Limit	%	AS1289 3.1.2	40			
100 mm	100			Plastic Limit	%	AS1289 3.2.1	18			
75 mm	100			Plasticity Index	%	AS1289 3.3.1	22			
53 mm	100			Linear Shrinkage	%	AS1289 3.4.1	ND			
37.5 mm	100			Moisture Content	%	AS1289 2.1.1	29.7			
26.5 mm	100			Sample History : Low Temp Oven Dried Preparation Method : Dry sieved Crumbling / Curling of Linear Shrinkage : - Linear Shrinkage Mould Length : - NP = non-plastic NO = not obtainable ND = not determined						
19.0 mm	100									
13.2 mm	100									
9.5 mm	100									
6.7 mm	100									
4.75 mm	100									
2.36 mm	100									
1.18 mm	100									
0.600mm	100									
0.425mm	99									
0.300mm	98									
0.150mm	95									
0.075mm	89									



	This document is issued in accordance with NATA's accreditation requirements.	 Darryl Murphy Laboratory Manager	20-Mar-12
	THIS DOCUMENT SHALL ONLY BE REPRODUCED IN FULL	AUTHORISED SIGNATORY	DATE


PARTICLE SIZE DISTRIBUTION & CONSISTENCY LIMITS TEST REPORT



Client	Ports North	Job Number	107672522-5000
Client Address	Cnr Grafton and Hartley Streets, Cairns, Qld 4870	Date	16-Mar-12
Project	Dredge Material Assessment	Report Number	NQ-12099
Location	Cairns Shipping Channel	Page No	1 of 1
Lab Ref No.	12/7061	Sampling Method	As Supplied to Laboratory
		Sample Identification	TP2 0.0-0.0.7m

Laboratory Specimen Description CI CLAY, medium plasticity, pale grey brown, with trace of sand.
 (AS1726, App A, Sect 2)

PARTICLE SIZE DISTRIBUTION AS1289 3.6.1				CLASSIFICATION LIMITS AND MOISTURE CONTENT						
Sieve Size	% Passing	Spec. Lower	Spec. Upper	Test	Method	Result	Spec. Lower	Spec. Upper		
150 mm	100			Liquid Limit	% AS1289 3.1.2	37				
100 mm	100			Plastic Limit	% AS1289 3.2.1	18				
75 mm	100			Plasticity Index	% AS1289 3.3.1	19				
53 mm	100			Linear Shrinkage	% AS1289 3.4.1	ND				
37.5 mm	100			Moisture Content	% AS1289 2.1.1	27.0				
26.5 mm	100			Sample History : Low Temp Oven Dried Preparation Method : Dry sieved Crumbling / Curling of Linear Shrinkage : - Linear Shrinkage Mould Length : - NP = non-plastic NO = not obtainable ND = not determined						
19.0 mm	100									
13.2 mm	100									
9.5 mm	100									
6.7 mm	100									
4.75 mm	100									
2.36 mm	100									
1.18 mm	99									
0.600mm	97									
0.425mm	96									
0.300mm	95									
0.150mm	92									
0.075mm	85									

PARTICLE SIZE DISTRIBUTION



	This document is issued in accordance with NATA's accreditation requirements.		
	THIS DOCUMENT SHALL ONLY BE REPRODUCED IN FULL	Darryl Murphy Laboratory Manager	20-Mar-12
		AUTHORISED SIGNATORY	DATE


0/01/1900



PARTICLE SIZE DISTRIBUTION & CONSISTENCY LIMITS TEST REPORT

Client	Ports North	Job Number	107672522-5000
Client Address	Cnr Grafton and Hartley Streets, Cairns, Qld 4870	Date	16-Mar-12
Project	Dredge Material Assessment	Report Number	NQ-12098
Location	Cairns Shipping Channel	Page No	1 of 1
Lab Ref No.	12/7060	Sampling Method	As Supplied to Laboratory
		Sample Identification	TP1 0.0-0.05m

Laboratory Specimen Description CH CLAY, high plasticity, pale grey and pale brown, with trace of sand.
 (AS1726, App A, Sect 2)

PARTICLE SIZE DISTRIBUTION AS1289 3.6.1				CLASSIFICATION LIMITS AND MOISTURE CONTENT					
Sieve Size	% Passing	Spec. Lower	Spec. Upper	Test		Method	Result	Spec. Lower	Spec. Upper
150 mm	100			Liquid Limit	%	AS1289 3.1.2	57		
100 mm	100			Plastic Limit	%	AS1289 3.2.1	17		
75 mm	100			Plasticity Index	%	AS1289 3.3.1	40		
53 mm	100			Linear Shrinkage	%	AS1289 3.4.1	ND		
37.5 mm	100			Moisture Content	%	AS1289 2.1.1	35.0		
26.5 mm	100			Sample History : Low Temp Oven Dried Preparation Method : Dry sieved Crumbling / Curling of Linear Shrinkage : - Linear Shrinkage Mould Length : - NP = non-plastic NO = not obtainable ND = not determined					
19.0 mm	100								
13.2 mm	100								
9.5 mm	100								
6.7 mm	100								
4.75 mm	100								
2.36 mm	100								
1.18 mm	99								
0.600mm	96								
0.425mm	94								
0.300mm	93								
0.150mm	91								
0.075mm	90								



	This document is issued in accordance with NATA's accreditation requirements.	 Darryl Murphy Laboratory Manager	20-Mar-12
	THIS DOCUMENT SHALL ONLY BE REPRODUCED IN FULL	AUTHORISED SIGNATORY	DATE

LABORATORY REPORT COVERSHEET

Date: 16 March 2012

To: Golder Associates Pty Ltd
PO Box 5823
CAIRNS QLD 4870

Attention: Jo Parisi

Your Reference: 107672522 Cairns Shipping Lane
Laboratory Report No: CE76936

Samples Received: 13/03/2012
Samples / Quantity: 8 Soils

The above samples were received intact and analysed according to your written instructions. Unless otherwise stated, solid samples are reported on a dry weight basis and liquid samples as received.



Jon Dicker
Manager
CAIRNS



Shey Goddard
Administration Manager
CAIRNS



CLIENT: Golder Associates Pty Ltd
PROJECT: 107672522 Cairns Shipping Lane

Laboratory Report No: CE76936

LABORATORY REPORT

Chromium Suite Our Reference Your Reference Type of Sample Date Sampled	Units	CE76936-1 TP1-001 Soil 2/03/2012	CE76936-2 TP2-001 Soil 2/03/2012	CE76936-3 TP2-003 Soil 2/03/2012
Date Extracted		13/03/2012	13/03/2012	13/03/2012
Date Analysed		13/03/2012	13/03/2012	13/03/2012
Moisture	% w/w	25	21	23
pH KCl	pH Units	9.3	7.7	7.7
TAA pH 6.5	kg H ₂ SO ₄ /tonne	<0.5	<0.5	<0.5
Chromium Reducible Sulfur (SCR)	% w/w	0.012	0.11	0.14
SHCl	% w/w	NA	NA	NA
S KCl	% w/w	NA	NA	NA
S NAS	% w/w	NA	NA	NA
Acid Neutralisation Capacity ANC _{BT}	% CaCO ₃	NA	1.6	1.1



CLIENT: Golder Associates Pty Ltd
PROJECT: 107672522 Cairns Shipping Lane

Laboratory Report No: CE76936

LABORATORY REPORT

Chromium Suite Our Reference Your Reference Type of Sample Date Sampled	Units	CE76936-4 TP3-001 Soil 1/03/2012	CE76936-5 TP3-003 Soil 1/03/2012	CE76936-6 TP4-001 Soil 1/03/2012
Date Extracted		13/03/2012	13/03/2012	13/03/2012
Date Analysed		13/03/2012	13/03/2012	13/03/2012
Moisture	% w/w	39	42	51
pH KCl	pH Units	8.7	8.7	9.0
TAA pH 6.5	kg H ₂ SO ₄ /tonne	<0.5	<0.5	<0.5
Chromium Reducible Sulfur (SCR)	% w/w	1.7	1.7	0.40
SHCl	% w/w	NA	NA	NA
S KCl	% w/w	NA	NA	NA
S NAS	% w/w	NA	NA	NA
Acid Neutralisation Capacity ANCBT	% CaCO ₃	2.2	3.0	9.0

Chromium Suite Our Reference Your Reference Type of Sample Date Sampled	Units	CE76936-7 TP5-001 Soil 1/03/2012	CE76936-8 TP5-003 Soil 1/03/2012
Date Extracted		13/03/2012	13/03/2012
Date Analysed		13/03/2012	13/03/2012
Moisture	% w/w	42	25
pH KCl	pH Units	8.7	7.9
TAA pH 6.5	kg H ₂ SO ₄ /tonne	<0.5	<0.5
Chromium Reducible Sulfur (SCR)	% w/w	1.4	1.1
SHCl	% w/w	NA	NA
S KCl	% w/w	NA	NA
S NAS	% w/w	NA	NA
Acid Neutralisation Capacity ANCBT	% CaCO ₃	4.4	0.6

CLIENT: Golder Associates Pty Ltd
PROJECT: 107672522 Cairns Shipping Lane

Laboratory Report No: CE76936

LABORATORY REPORT

TEST PARAMETERS	UNITS	LOR	METHOD
Chromium Suite			
Date Extracted			
Date Analysed			
Moisture	% w/w	0.1	AN002 RL2A1
pH KCl	pH Units	0.1	AS4969.2 / AN219
TAA pH 6.5	kg H ₂ SO ₄ /tonne	0.5	AS4969.2 / AN219
Chromium Reducible Sulfur (SCR)	% w/w	0.005	AS4969.7
SHCl	% w/w	0.005	AS4969.8 / AN014
S KCl	% w/w	0.005	AS4969.4
S NAS	% w/w	0.005	AS4969.11
Acid Neutralisation Capacity ANCBT	% CaCO ₃	0.1	AN214

CLIENT: Golder Associates Pty Ltd
PROJECT: 107672522 Cairns Shipping Lane

Laboratory Report No: CE76936

LABORATORY REPORT

QUALITY CONTROL	UNITS	Blank	Duplicate Sm#	Duplicate Sample Duplicate	Spike	CMS Recovery
Date Extracted		13/03/12	CE76936-1	13/03/2012 13/03/2012	Batch Spike	13/03/12
Date Analysed		13/03/12	CE76936-1	13/03/2012 13/03/2012	Batch Spike	13/03/12
Moisture	% w/w	-	CE76936-1	25 [N/T]	Batch Spike	-
pH KCl	pH Units	5.2	CE76936-1	9.3 9.4 RPD: 1	Batch Spike	99%
TAA pH 6.5	kg H ₂ SO ₄ /tonne	-	CE76936-1	<0.5 <0.5	Batch Spike	93%
Chromium Reducible Sulfur (SCR)	% w/w	-	CE76936-1	0.012 0.015 RPD: 22	Batch Spike	100%
SHCl	% w/w	-	CE76936-1	NA NA	Batch Spike	-
S KCl	% w/w	-	CE76936-1	NA NA	Batch Spike	-
S NAS	% w/w	-	CE76936-1	NA NA	Batch Spike	-
Acid Neutralisation Capacity ANCBT	% CaCO ₃	-	CE76936-1	NA NA	Batch Spike	-

CLIENT: Golder Associates Pty Ltd
PROJECT: 107672522 Cairns Shipping Lane

Laboratory Report No: CE76936

LABORATORY REPORT

NOTES:

LOR - Limit of Reporting.

The significance of all reported results are defined by their analytical limit of reporting.

Liming rate calculated using a Fineness factor of 1.5 (which is equivalent to finely divided Ag Lime <0.5mm) and Neutralising Value (NV) of 100%

If using Liming Material <100% NV, then Liming Rate can be adjusted as follows:

Actual Liming Rate equals Calculated Liming Rate times 100 divided by NV of actual Liming Material

Bulk Density of Material of 1g/cm³ assumed.

If Bulk Density differs from 1g/cm³ then Liming rate can be adjusted as follows:

Actual Liming Rate equals Calculated Liming Rate times Actual Bulk Density

Geneva Legal Comment

This document is issued by the Company subject to its General Conditions of Service (www.sgs.com/terms_and_conditions.htm).

Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein.

This document is to be treated as an original within the meaning of UCP 600. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any.

The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ISO 17025

Unless otherwise stated the results shown in this test report only refer to the sample(s) tested and such sample(s) are only retained for 60 days only. This document cannot be reproduced except in full, without prior approval of the Company.

Analysis Date: Between 13/03/12 and 16/03/12

Disclaimer:

SGS and the authors have prepared this document in good faith, consulting with Ahern CR, McElnea AE, Sullivan LA (2004)

Acid Sulphate Soils Laboratory Methods Guidelines,

Queensland Department of Natural Resources, Mines and Energy, Indooroopilly, Qld Aust.

While this is done exercising all due care and attention, no representation or warranty, expressed or implied is made as to the accuracy, completeness or fitness of the document in respect of any user's circumstances.

Users of the results or data should seek appropriate expert advice where necessary in relation to their particular situation or circumstances.

Any representation, statement, opinion or advice, expressed or implied on this publication


is made in good faith and on the basis that SGS, its agents and employees are not liable to any person taking or not taking (as the case may be) action in respect of any representation, statement or advice referred to above.

SGS Terms and Conditions are available from www.au.sgs.com

Page 6 of 6

TRIAXIAL SHEAR TEST

Client :	Ports North	Report No. :	R12466
Address :	Corner Grafton & Hartley Streets, Cairns	Job No. :	107672522-5000
Project :	Dredge Material Assessment	Reg'n No. :	12301151
Location :	PN-TP3-003, CH 17683 (10.9m)	Sample No. :	
Date of Test :	20/03/12	Sampled By :	Client
Type of test :	Unsaturated, Unconsolidated, Undrained, Staged		
Sample Type :	Undisturbed	Strain Rate :	0.50 mm/min
Specimen Diameter :	47.0 mm	Specimen Height :	94.5 mm
Initial Moisture Content :	64.3 %	Initial Saturation :	98 %
Initial Dry Density :	0.97 t/m ³		



Stage	Initial Cell Pressure (kPa)	Maximum Principal Stress (kPa) σ_1	Minimum Principal Stress (kPa) σ_3	Maximum Deviator Stress (kPa)	Failure Strain (%)
1	30	43	30	13	0.8
2	60	75	60	15	2.1
3	120	141	120	21	19.0

Failure Criteria : Maximum Shear Stress
Remarks : Shear plane at 45° after test.
Material Description : (CH) Silty CLAY, dark grey
Test Procedure : AS1289.6.4.1

Prepared by *nk*

Checked by *nk*



BRISBANE LABORATORY

28 Bank Street, West End QLD 4101

PO Box 3427 South Brisbane BC QLD 4101


Phone: (07) 3840 9500 Fax: (07) 3840 9501

www.golder.com.au

TRIAxIAL SHEAR TEST (STRESS STRAIN GRAPH)

Client : Ports North
 Address : Corner Grafton & Hartley Streets, Cairns
 Project : Dredge Material Assessment
 Location : PN-TP3-003, CH 17683 (10.9m)


Report No. : R12466
 Job No. : 107672522-5000
 Reg'n No. : 12301151
 Sample No. :
 Sampled By : Client

Prepared by *mt*Checked by *LH*

TRIAxIAL SHEAR TEST

Client :	Ports North	Report No. : R12467
Address :	Corner Grafton & Hartley Streets, Cairns	Job No. : 107672522-5000
Project :	Dredge Material Assessment	Reg'n No. : 12301152
Location :	PN-TP3-004, CH 17683 (12.7m)	Sample No. :
Date of Test :	21/03/12	Sampled By : Client

Type of test :	Unsaturated, Unconsolidated, Undrained, Staged		
Sample Type :	Undisturbed	Strain Rate :	0.50 mm/min
Specimen Diameter :	47.0 mm	Specimen Height :	94.7 mm
Initial Moisture Content :	63.0 %	Initial Saturation :	100 %
Initial Dry Density :	1.00 t/m ³		



Stage	Initial Cell Pressure (kPa)	Maximum Principal Stress (kPa) σ_1	Minimum Principal Stress (kPa) σ_3	Maximum Deviator Stress (kPa)	Failure Strain (%)
1	30	50	30	20	1.6
2	60	82	60	22	2.4
3	120	149	120	29	9.5

Failure Criteria :	Maximum Shear Stress
Remarks :	Shear plane at 45° after test.
Material Description :	(CH) Silty CLAY, dark grey
Test Procedure :	AS1289.6.4.1

Prepared by *MF*

Checked by *GH*

This document is issued in accordance with NATA's accreditation requirements.



Nick Farrer

Approved Signatory

Senior Technical Officer

NATA Accred. No. : 1961

Golder Form No. R19
RL1 - 29/01/08



BRISBANE LABORATORY

28 Bank Street, West End QLD 4101


PO Box 3427 South Brisbane BC QLD 4101

Phone: (07) 3840 9500 Fax: (07) 3840 9501

www.golder.com.au


TRIAxIAL SHEAR TEST (STRESS STRAIN GRAPH)

Client :	Ports North	Report No. :	R12467
Address :	Corner Grafton & Hartley Streets, Cairns	Job No. :	107672522-5000
Project :	Dredge Material Assessment	Reg'n No. :	12301152
Location :	PN-TP3-004, CH 17683 (12.7m)	Sample No. :	
		Sampled By :	Client

Prepared by *mk*Checked by *ct*

TRIAxIAL SHEAR TEST

Client :	Ports North	Report No. :	R12468
Address :	Corner Grafton & Hartley Streets, Cairns	Job No. :	107672522-5000
Project :	Dredge Material Assessment	Reg'n No. :	12301153
Location :	PN-TP5-002, CH 22508 (12.1m)	Sample No. :	
Date of Test :	21/03/12	Sampled By :	Client
Type of test :	Unsaturated, Unconsolidated, Undrained, Staged		
Sample Type :	Undisturbed	Strain Rate :	0.50 mm/min
Specimen Diameter :	47.0 mm	Specimen Height :	94.4 mm
Initial Moisture Content :	85.9 %	Initial Saturation :	98 %
Initial Dry Density :	0.80 t/m ³		



Stage	Initial Cell Pressure (kPa)	Maximum Principal Stress (kPa) σ_1	Minimum Principal Stress (kPa) σ_3	Maximum Deviator Stress (kPa)	Failure Strain (%)
1	30	44	30	14	0.5
2	60	74	60	14	1.1
3	120	137	120	17	7.4

Failure Criteria : Maximum Shear Stress
Remarks : Shear plane at 45° after test.
Material Description : (CH) Silty CLAY, dark grey
Test Procedure : AS1289.6.4.1

Prepared by *mf*

Checked by *glt*

This document is issued in accordance with NATA's accreditation requirements.



Nick Farrer

Approved Signatory

Senior Technical Officer

NATA Accred. No. : 1961

Golder Form No. R19
RL1 - 29/01/08



BRISBANE LABORATORY

28 Bank Street, West End QLD 4101


PO Box 3427 South Brisbane BC QLD 4101

Phone: (07) 3840 9500 Fax: (07) 3840 9501

www.golder.com.au


TRIAXIAL SHEAR TEST (STRESS STRAIN GRAPH)

Client :	Ports North	Report No. :	R12468
Address :	Corner Grafton & Hartley Streets, Cairns	Job No. :	107672522-5000
Project :	Dredge Material Assessment	Reg'n No. :	12301153
Location :	PN-TP5-002, CH 22508 (12.1m)	Sample No. :	
		Sampled By :	Client

Prepared by *mc*Checked by *h*

TRIAXIAL SHEAR TEST

Client :	Ports North	Report No. :	R12469
Address :	Corner Grafton & Hartley Streets, Cairns	Job No. :	107672522-5000
Project :	Dredge Material Assessment	Reg'n No. :	12301154
Location :	PN-TP5-004, CH 22508 (12.75m)	Sample No. :	
Date of Test :	21/03/12	Sampled By :	Client
Type of test :	Unsaturated, Unconsolidated, Undrained, Staged		
Sample Type :	Undisturbed	Strain Rate :	0.50 mm/min
Specimen Diameter :	47.0 mm	Specimen Height :	94.4 mm
Initial Moisture Content :	35.8 %	Initial Saturation :	66 %
Initial Dry Density :	1.10 t/m ³		



Stage	Initial Cell Pressure (kPa)	Maximum Principal Stress (kPa) σ_1	Minimum Principal Stress (kPa) σ_3	Maximum Deviator Stress (kPa)	Failure Strain (%)
1	30	48	30	18	0.5
2	60	85	60	25	1.3
3	120	162	120	42	15.9

Failure Criteria : Maximum Shear Stress
Remarks : Shear plane at 45° after test.
Material Description : (CH) Silty CLAY, dark grey
Test Procedure : AS1289.6.4.1

Prepared by *mk*

Checked by *LH*

This document is issued in accordance with NATA's accreditation requirements.



Nick Farrer

Approved Signatory

Senior Technical Officer

NATA Accred. No. : 1961

Golder Form No. R19
RL1 - 29/01/08



BRISBANE LABORATORY

28 Bank Street, West End QLD 4101

PO Box 3427 South Brisbane BC QLD 4101


Phone: (07) 3840 9500 Fax: (07) 3840 9501

www.golder.com.au

TRIAxIAL SHEAR TEST (STRESS STRAIN GRAPH)

Client : Ports North
 Address : Corner Grafton & Hartley Streets, Cairns
 Project : Dredge Material Assessment
 Location : PN-TP5-004, CH 22508 (12.75m)

Report No. : R12469
 Job No. : 107672522-5000
 Reg'n No. : 12301154
 Sample No. :
 Sampled By : Client

Prepared by *mk*Checked by *h4*

Test Location	Depth Range (m - BGL)	Material Description	pH _{FIELD}	pH _{KCl}	TAA (kg H ₂ SO ₄ /tonne)	sTAA Converted to %S*	S _{NAS} (if pH less than 4.5)	Existing Acidity %S (sTAA + 0.75 x S _{NAS})	Chromium Reducible Sulfur (S _{CR}) %S	Acid Neutralising Capacity %CaCO ₃ (if pH more than 6.5)	Net Acidity %S (S _{CR} +Existing Acidity - ANC/FF)	Is This AASS	Is This PASS	Liming Rate for Net Acidity (Neutralises both AASS & PASS) (kg/m3)
PN-TP1-001	0.0-0.5	CLAY, CH	8.27	9.3	< 0.5	< 0.016		0.000	0.012	0	0.012	No	No	NA
PN-TP2-001	0.0-0.7	CLAY, CI	6.76	7.7	< 0.5	< 0.016		0.000	0.110	1.6	-0.232	No	YES	No Additional Lime Required
PN-TP2-003	1.6-1.7	CLAY, CI	6.76	7.7	< 0.5	< 0.016		0.000	0.140	1.1	-0.095	No	YES	No Additional Lime Required
PN-TP3-001	1.5-2.8	CLAY, CH	7.39	8.7	< 0.5	< 0.016		0.000	1.700	2.2	1.230	No	YES	93.0
PN-TP3-003	2.8-3.2	CLAY, CH	7.23	8.7	< 0.5	< 0.016		0.000	1.700	3	1.059	No	YES	80.1
PN-TP4-001	3.3-3.4	CLAY, CH	7.76	9.0	< 0.5	< 0.016		0.000	0.400	9	-1.522	No	YES	No Additional Lime Required
PN-TP5-001	2.5-2.9	CLAY, CH	7.59	8.7	< 0.5	< 0.016		0.000	1.400	4.4	0.460	No	YES	34.8
PN-TP5-003	2.9-3.6	CLAY, CH	6.23	7.9	< 0.5	< 0.016		0.000	1.100	0.6	0.972	No	YES	73.5

Note: * Equivalent oxidisable sulfur calculated as TAA/30.59
Liming rates assume a bulk density of 1.60 t/m3
Fineness Factor = 1.5

TABLE 1
SUMMARY OF ACID SULFATE TEST RESULTS

Client Ports North
Job Title Dredge Material Assessment
Location Cairns Shipping Channel



pH FIELD TESTS

Method: As per the Guidelines for Sampling and Analysis of Lowland Acid Sulfate Soils (ASS) in Queensland 1998.

Client : Ports North	Project Number : 107672522 - 5000
Project : South Foreshore - Dredge Assessment	Tested By/Date : CWG - 8/03/2012
Location : Trinity Inlet Shipping Lane	Checked By / Date :

pH Meter No. : Gac501	pH Peroxide : 4.05
Date pH Meter Calibrated : 8/01/2012	pH Distilled Water : 5.92

Hole No.	Depth (m)	Soil Type	pH	pH fox	reaction	PASS Potential		
						high	medium	low
PN-TP1-001	0.0-0.5m	soft clay	8.3	6.4	very slight			
PN-TP2-001	0.0-0.7m	soft clay	6.8	5.4	slight			
PN-TP2-003	1.6-1.7m	firm clay	6.8	4.4	slight			
PN-TP-3-001	1.5-2.8m	soft clay	7.4	4.9	veryreactive			
PN-TP-3-003	2.8-3.2m	firm clay	7.2	3.0	veryreactive			
PN-TP4-001	3.3-3.4m	soft clay	7.8	5.8	moderatelyreactive			
PN-TP5-001	2.5-2.9m	soft clay	7.6	5.1	veryreactive			
PN-TP3-003	2.9-3.6m	firm clay	6.2	2.8	veryreactive			



Golder Boreholes 2013