



CLIENTS | PEOPLE | PERFORMANCE

Dyno Nobel Asia Pacific
Limited

**Moranbah Ammonium Nitrate
Project**

Wastewater Management Report
August 2006



Contents

1.	Introduction	1
1.1	Background	1
1.2	General Development Description	1
1.3	Scope	1
2.	Description of Study Area	3
2.1	Location	3
2.2	Geology	5
2.3	Climate	5
3.	Design Wastewater Flows	7
3.1	Overview	7
3.2	Temporary Facilities	8
3.3	Permanent Facilities	8
3.4	Design Data	8
4.	Wastewater Treatment Technologies	10
4.1	Overview	10
4.2	Membrane Bioreactors (MBR)	10
4.3	Activated Sludge Package Plant	11
4.4	Biolytix Filters	11
4.5	Combination of Composting Toilets and Greywater Recycling	13
4.6	Summary of Wastewater Treatment Options	14
5.	Separate Irrigation System Requirements	16
5.1	Overview	16
5.2	Recycled Water System	16
5.3	Wet Weather Storage Sizing	16
5.4	Nutrient Balance and Irrigation Area Sizing	17
6.	Combined Irrigation System Requirements	20
6.1	Overview	20
6.2	Wastewater Characteristics	20
6.3	MEDLI results	20
7.	Cost Estimates	21



7.1	Overview	21
7.2	Cost Estimates	21
7.3	Basis of Estimate – Capital Costs	23
8.	Discussion of Relative Merits	25
8.1	Overview	25
9.	Conclusion and Recommendation	28
9.1	Conclusion	28
9.2	Recommendations	28

Table Index

Table 1	Climate data for Moranbah	6
Table 2	Typical Proportions of Wastewater Sources	7
Table 3	Wastewater Proportions	9
Table 4	Design Wastewater Characteristics	9
Table 5	Wastewater Treatment Options	14
Table 6	Summary of Design Effluent Flows and Qualities	15
Table 7	Proposed Wet Weather Storage Volumes	17
Table 8	Summary of MEDLI results	17
Table 9	Soil Sensitivity Analyses	19
Table 10	Indicative Capital Costs - Permanent Domestic Wastewater	21
Table 11	Indicative Capital Costs – Temporary Construction Accommodation	22
Table 12	Indicative Capital Costs – Temporary Construction Accommodation with Composting Toilets	22
Table 13	Advantages and Disadvantages of Each Option	26
Table 14	Standard MEDLI Profile: Sand	32
Table 15	Standard MEDLI Profile: Grey Clay	33
Table 16	MEDLI Soil Profile Adopted to Represent “Clayey Sand”	34
Table 17	Design Parameters	36
Table 18	Summary of MEDLI Input Parameters – Temporary Accommodation	38
Table 19	Summary of MEDLI Input Parameters – Permanent Facilities	39
Table 20	Summary of MEDLI Input Parameters – Temporary Accommodation with Composting Toilets	40



Table 21	Summary of MEDLI Input Parameters – Temporary Accommodation with Composting Toilets	41
----------	---	----

Figure Index

Figure 1:	Proposed Moranbah Site Location	4
Figure 2:	Plot of Rainfall vs Pan Evaporation for Moranbah	6
Figure 3:	Cross-section of Biolytix™ Filter. Source: Biolytix Pty Ltd.	12
Figure 4:	Biolytix™ Filter – BF6 treatment unit.	12

Appendices

- A Borehole Logs
- B MEDLI soil profiles
- C Wastewater Design Parameters
- D MEDLI Input Data



1. Introduction

1.1 Background

GHD were commissioned to investigate the feasibility of different wastewater management systems for a proposed ammonium nitrate plant at Moranbah. GHD understand that the proposed works will include an ammonium nitrate plant, emulsion plant, raw water reservoir, power generation facility and evaporation pond.

GHD understand that the proposed development will have access to municipal water supply on Goonyella Road, however wastewater is to be recycled and disposed of on-site.

This investigation considers the treatment and irrigation of **domestic** wastewater (namely wastewater sourced from toilets, laundry, basins, showers, kitchen facilities) on site. It does not consider either the treatment of wastewater from the ammonium nitrate plant or the design of the associated evaporation pond.

This desk-top assessment compares the viability of different wastewater treatment and management options to service both permanent staff at the facility, and the temporary accommodation units of construction staff.

1.2 General Development Description

Dyno Nobel Asia Pacific Limited (DN) is seeking to construct and operate a new ammonium nitrate plant and an emulsions manufacturing plant approximately 4 kilometres north-west of Moranbah. The combined plants would produce ammonium nitrate emulsion (a viscous liquid) and prill (a solid). The project would be an addition to its existing QNP facility at Moura.

1.3 Scope

This report only considers wastewater treatment/management options regarded as potentially appropriate at the site. Two different wastewater management systems will be considered:

Option 1	To manage wastewater from the temporary accommodation and from the permanent facilities in two separate systems. It is envisaged that wastewater from the temporary works will be treated by a package plant before irrigation of the recycled water to nearby land. Separate treatment would be provided for the permanent toilet facilities associated with the plant, and it is expected that this recycled water will be directed to the ammonium nitrate plant's evaporation ponds.
Option 2	To recycle water to irrigation from both permanent and temporary sources. While it is likely to be more efficient to still construct two separate wastewater treatment plants (one permanent and one temporary), recycled water from both sources would be irrigated. One advantage of irrigating recycled water from the evaporation pond is that it should allow the evaporation pond volume to be reduced.



The works undertaken in this report consist of:

- » Determining the wastewater flows expected from both temporary and permanent facilities;
- » Outlining options for wastewater treatment;
- » Determining (to a conceptual level of detail) expected nutrient concentrations in the effluent for the different treatment technologies;
- » Using the design flows and nutrient concentrations to run MEDLI (Model for Effluent Disposal Using Land Irrigation) models. The MEDLI modelling will quantify the rates of sustainable irrigation of treated wastewater on site, and the irrigation areas required;
- » Providing indicative cost estimates; and
- » Identifying advantages and disadvantages of the different wastewater management options.



2. Description of Study Area

2.1 Location

The proposed ammonium nitrate plant location is shown in Figure 1.

Figure 1 illustrates the location of the ammonium nitrate plant site and the proposed temporary accommodation site. Please note that the 'irrigation area' shown adjacent to the accommodation camp is intended as a general indication of the area put aside for irrigation from the camp and it includes setback distances to roads and the camp. It is not proposed that the entire 7 hectare area is irrigated.



Date: 02-10-06 Rev C
 Datum: GDA94 (MGA) Zone 55
 Source: Base data sourced from the State of Queensland, Department of Natural Resources, Mines. All other infrastructure supplied by Dyno Nobel Asia Pacific Ltd.
 File: G:\4115824\GIS\Maps\Final\MXD\fig_1_Site_Location_RevC.mxd

Legend


- Ammonium Nitrate Plant Site
- Evaporation Pond
- Generating Facility*
- Raw Water Reservoir
- Cadastre
- Easements
- Developed Area
- Watercourse
- Major Road
- Railway
- Powerlines

*Generating Facility location is subject to detailed engineering.

Moranbah Ammonium Nitrate Plant

Environmental Impact Statement

Figure 1 Site Location



Copyright: This document is and shall remain the property of GHD Pty Ltd. The document may only be used for the purpose for which it was commissioned and in accordance with the terms of engagement for the commission. Unauthorised use of this document in anyway is prohibited.



2.2 Geology

Coffey Geoscience Pty Ltd drilled a number of boreholes on the ammonium nitrate plant site as part of a separate investigation. Copies of the eleven borehole logs are included in Appendix A.

The majority of the borehole logs are clayey sand, with sandy clay, clay and gravelly clayey sand also featured. The highest depth at which 'rock material' occurred was 4.5 m and generally rock material was not encountered til at least 10 m. The borehole closest to the proposed irrigation area for the temporary accommodation shows a clayey sand and it was assumed that this soil type represents all irrigation areas.

Clayey sand is not included in the standard MEDLI soil profiles. So to model the soil behaviour a new soil profile was created. The new soil profile was an amalgam of the standard "Sand" and standard "Grey Clay" profiles. The new soil characteristics were based more strongly on sand than grey clay, as sand was dominant in the soil classification. The upper and lower storage limits of the new soil profile were based on those for 'loamy clay' in Table 6.3 of the MEDLI Reference Manual¹. Both the new and standard soil parameters used are included in Appendix B for reference.

2.3 Climate

Daily climate data (from 1957 to 2005) for Moranbah was sourced from the Department of Natural Resources, Mines and Water (DNRW). DNRW derived the data based on the location of the town (22° 00' S and 148° 05' E) in relation to the location of weather stations. The climate data used for the MEDLI analysis is summarised in Table 1.

The site has a dry climate with an average annual rainfall of only 964 mm. Pan evaporation consistently exceeds rainfall on an average monthly basis (Figure 2). The dry climate facilitates the use of on-site irrigation systems to dispose of treated wastewater.

¹ GARDNER T., DAVIES (1998) *MEDLI Reference Manual*.



Table 1 Climate data for Moranbah

Monthly	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sept	Oct	Nov	Dec	Year
Rainfall (mm)	92	90	58	36	33	20	18	23	8	33	63	99	572
Pan Evap (mm)	233	188	197	153	120	97	108	136	181	226	234	246	2119
Ave Max Temp (°C)	33	33	32	29	26	24	24	25	29	32	33	34	29
Ave Min Temp (°C)	22	22	20	17	14	10	9	10	13	17	20	21	16
Rad (MJ/m ² /day)	22	21	20	18	15	15	16	19	22	24	24	24	19




Figure 2: Plot of Rainfall vs Pan Evaporation for Moranbah



3. Design Wastewater Flows

3.1 Overview

This investigation considers wastewater flows generated from permanent and temporary facilities. Recycled water will be irrigated on site, so it was determined that the design wastewater generation rates included in *The On-site Domestic Wastewater Management Code (AS/NZS 1547:2000)* were the most appropriate to be adopted in this study.

The design loading rates for a dwelling with a reticulated water supply listed in Appendix 4.2D of *The On-site Domestic Wastewater Management Code* are:

- » 180 L/EP/day for households with 'standard fixtures' (ie without water conservation fittings);
- » 145 L/EP/day for a dwelling with 'standard' water conservation fixtures; and
- » 110 L/EP/day for a dwelling with full water-reduction fittings.

While the development will have at least standard water conservation fittings (such as dual flush toilets), 180 L/EP/day will be adopted in this investigation as representative of a dwelling with laundry, showers, kitchen facilities and flushing toilets. The additional flow allowance will act as a factor of safety.

The flow allowance of 180 L/EP/day is adjusted to account for which wastewater producing fixtures (eg toilets, showers etc) are being used for each facility. The basis for the adjustment is the typical proportion of wastewater source characteristics cited in DNRW's *Planning Guidelines for Water Supply and Sewerage*² (Table 2).

Table 2 Typical Proportions of Wastewater Sources

Component	Usual Proportions in Wastewater
Toilets	26%
Bath/Shower	34%
Kitchen	13%
Laundry	22%
Other	5%

A description of both the temporary and permanent facilities and the design flows adopted are outlined in the following sections.

² DEPARTMENT OF NATURAL RESOURCES AND MINES (March 2005) *Planning Guidelines for Water Supply and Sewerage*.



3.2 Temporary Facilities

Temporary accommodation will be provided at the site for construction staff. It is understood that accommodation for the site will include individual rooms with en-suite (i.e. showers and toilets). Communal laundry facilities will also be provided.

Wastewater management for temporary accommodation will be required for a peak of 550 construction staff from 18 months to 2 years. After this time, the temporary accommodation will be re-used and any wastewater management systems will be decommissioned. This advice was current when this report was prepared, although it is understood from recent advice that DN may consider making the construction accommodation a more permanent facility. For this report, it is assumed that the construction accommodation is temporary in nature.

It has been assumed that staff will build up to a peak of 550, and perhaps reduce back down to a lower level prior to commissioning of the ammonium nitrate plant. The wastewater treatment and management systems considered to a conceptual level in this report should be robust for this scheduling of variation in loads. Should the staff be expected to oscillate substantially over short periods of time (eg from 550 down to 200 then back to 550 etc) the use of biological treatment systems should be reconsidered. Biological systems which can cater for a progressive increase and reduction in loads are favoured in this report as they allow a good level of nutrient reduction, which in turn reduces the area (and costs) required for sustainable irrigation.

One of the wastewater management options considered in this investigation is the use of composting toilets for the temporary construction camp. The use of composting toilets will reduce the volume of wastewater to be irrigated and the total amount of nutrients in the wastewater. These factors act to reduce the area required for irrigation, and therefore to potentially reduce the investment in infrastructure that is expected to become redundant two years after establishment.

The treatment systems considered are outlined in more detail in Section 4 of this report.

3.3 Permanent Facilities

Wastewater management will be required for approximately 75 permanent staff. It is understood that the permanent workers will work on two 12 hour shifts, specifically that only 38 staff will be on-site at any one time.

The facilities to service the permanent staff are:

- » A small kitchen facility;
- » Toilets; and
- » Showers.

3.4 Design Data

The flow rates have been based on a total possible per capita flow of 180 l/EP/d (AS/NZS 1547:2000). The design flow rates have been pro-rated from this value based on the following values in Table 3.



Table 3 Wastewater Proportions

Component	Usual Proportions in Wastewater	Permanent Facilities	Temporary Facilities	Temporary Facilities (with Composting Toilets)
Toilets	26%	26%	26%	4%
Bath/Shower	34%	17%	34%	34%
Kitchen	13%	13%	13%	13%
Laundry	22%	0%	22%	22%
Other	5%	5%	5%	5%

Please note the following:

- » The permanent staff will not be resident at the process plant and are therefore assumed to use only 50% of the usual bath/shower use.
- » The Temporary facilities are assumed to use the same proportion of flow as a 'typical' permanent dwelling.
- » Permanent staff will use an off-site laundry, while temporary staff will share communal laundry facilities.
- » Composting toilets are expected to result in a lower per capita flow than where more conventional flushing toilets are used.

The expected design characteristics of the wastewater based on the wastewater proportions are included in Appendix C and flow and nutrient quality of untreated wastewater are summarised in Table 4.

Table 4 Design Wastewater Characteristics

	Flow rate adopted (L/EP/day)	EP	Flow (kL)	TN (mg/L)	TP (mg/L)
Temporary	180	560	100.8	74	13
Permanent	110	38	4.18	120	21.5
Temporary - composting toilets option	140	550	77	96	16.9



4. Wastewater Treatment Technologies

4.1 Overview

A number of treatment technologies were considered for the two different situations - permanent staff and temporary staff. In both cases the option of using an Membrane Bioreactors (MBR), package activated sludge plant or Biolytix plant was investigated. In the case of the temporary staff combining one of these process options with composting toilet facilities was also investigated.

It was not considered beneficial to combine the wastewater from the permanent and temporary staff due to the problems that would be encountered when the high flow and load from the temporary staff was removed from the system after the two year construction phase.

The temporary construction staff are expected to reach a maximum of 550 EP and it is likely that there will be a staged increase in the number of staff present on site. A practical approach to the provision of wastewater treatment for any process would be to provide 3 stages of growth. Each stage could have a capacity of approximately 200 EP and would be brought on-line and decommissioned according to the population present on site.

4.2 Membrane Bioreactors (MBR)

MBRs have been developed overseas relatively recently (Canada, Japan, UK and Europe) and have been constructed in limited applications in Australia (GHD was involved in the design and commissioning of Australia's first membrane bioreactor at Picnic Bay on Magnetic Island). In MBRs, the concept is to amalgamate an activated sludge reactor with a membrane filtration plant to produce a hybrid reactor-separation step that does not require an intermediate secondary clarifier, thereby reducing the plant footprint. The membranes are immersed inside the activated sludge reactor. In order to minimise fouling of the membranes with the high solids concentration in the activated sludge reactor, the liquid surrounding the membranes is rapidly agitated, usually by coarse bubble aeration.

MBRs have the potential to produce very high effluent quality - the effective pore of the membranes is equivalent to ultrafiltration, which removes protozoa, bacteria and a significant fraction of viruses. The provision of an anoxic tank and recycle between the membrane tank and the anoxic tank allows for the removal of total nitrogen from the wastewater. The removal of total phosphorus is carried out using alum dosing.

The effluent quality from an MBR system in terms of nutrient quality is dependant on the sludge age of the biological process. With a low sludge age of approximately 5 days, the effluent nitrogen will be in the region of 11 mg/L (based on an anoxic zone and suitable recycles being included in the design). The effluent total phosphorous will be between 1 and 2 mg/L.



For the purposes of nutrient modelling, the MEDLI model will therefore assume the design effluent concentrations of 11 mg/L for nitrogen and 2 mg/L for phosphorous for both temporary and permanent facilities.³

4.3 Activated Sludge Package Plant

An activated sludge package plant could be used to provide a similar level of treatment, in terms of nutrient quality, to that produced by the MBR system. In addition to the activated sludge tank volume a final clarifier would be required to allow settlement of the mixed liquor. The waste mixed liquor would also have a lower concentration than that from the MBR therefore larger volumes of sludge would be produced and would probably require thickening before being transported off site.

The activated sludge process does not have the benefit of being equivalent to ultrafiltration therefore would be expected to have a much lower log removal of protozoa, bacteria and viruses than the MBR process.

For this investigation it was decided to look at the MBR process rather than the activated sludge process due to the improved performance in terms of disinfection and quantities of sludge produced. A cost/benefit comparison for the two processes could be compared at a later design stage to compare issues such as energy demand and maintenance requirements as well as capital costs.

4.4 Biolytix Filters

Biolytix™ Filters are a patented passive aerobic process. They are a relatively “natural” wastewater treatment system, primarily relying on biological treatment of wastes through vermiculture. Water that has been treated by the Biolytix filters is of better quality than that produced by septic tanks and it may be re-used via subsurface irrigation in gardens.

The filters consist of layered, flexible modular elements (as illustrated in Figure 3). The top layer of the filter system immediately separates solids from the raw sewage, which are broken down by worms and other organisms into a structured hummus. The organic matter particles then wash through and accumulate on the surface of a finely structured humus and coco-peat layer. The geotextile filters out remaining particles down to 90 micron. The biological filter unit requires only minimal maintenance as the organic processing of waste acts to maintain drainage pathways.

³ At the preliminary/ detailed design stages the design of the MBR will be adjusted to ensure these concentrations are achieved.




Figure 3: Cross-section of Biolytix™ Filter. Source: Biolytix Pty Ltd.

Biolytix™ Filters are typically applied in individual on-site systems, such as the BF6 filter. The treatment capabilities of Biolytix™ filters are telemetered and the effluent from BF6 filters is capable of being used for subsurface irrigation in gardens. An example of a BF6 treatment unit is shown in Figure 4.




Figure 4: Biolytix™ Filter – BF6 treatment unit.

The individual Biolytix treatment units are available in a range of sizes appropriate to treat different flows, including 3.3 kL, 6.6 kL and 10 kL sizes. The treatment units can also be linked in what is termed a “Biowater™ Network”, which links the individual treatment networks to a centralised storage and irrigation area.



The configuration of Biolytix filters can therefore be adapted (to an extent) to be compatible with the layout of the construction camp. For the purposes of this investigation, it is assumed that accommodation in the construction camp will be constructed in rows, and that the Biolytix filters will be placed between the rows. It is assumed that each Biolytix filters will receive waste from two units, and that separate Biolytix filters will be constructed for the laundry and the dining facilities. More detailed design will be possible when the layout of the camp is finalised and when topographical survey is completed.

Biolytix filters are certified for use in Queensland⁴, but there is no associated cited nutrient quality data.⁵ The Biolytix treatment filters achieved effluent concentrations of 50 mg/l TN and 9.1 mg/L for Macleay Island Biowater Scheme (Redlands Water), although the wastewater contained elevated levels of nutrients from the use of garbage grinder insinkers. Allowing for this, the average removal of nitrogen is predicted to be 50% so concentrations of 60 mg/l effluent TN for permanent facilities, 37 mg/l for temporary facilities and 35 mg/l for temporary facilities with composting toilets are predicted.

4.5 Combination of Composting Toilets and Greywater Recycling

A composting toilet is an alternative on-site, sanitation system for treating human excreta without the use of water for flushing. Bulking material (fibrous organic matter like vegetable scraps, sawdust, etc.) can be used to optimise the composting process. The composting toilet has a similar arrangement to standard water closets, although composting toilets might incorporate a urine separation device in the bowl.

In contrast to common perception, (well-managed) composting toilets do not smell. Composting toilets have been used sustainably in permanent applications, but it's considered that their most useful application for the DN site would be for the temporary facility.

The composting process is dependent on moisture content and maintaining an aerobic environment in the compost heap. The presence of liquid, i.e. urine, leachate and grey water, can affect the composting process adversely. High moisture content in the heap can lower internal temperature leading to slower degradation, and can minimise air contact with the organic matter. Source separation can therefore improve the performance of composting toilets, making the compost more stable. It is proposed that urine would be managed with the greywater system, and treated before it was applied on site.

While urine separating toilets are potentially available, it is anticipated that the majority of employees on the industrial construction camp in a remote location would be men and that the more economical options of urinals is viable. Composting toilets can accommodate some urine as they are vented so it is not anticipated that use by a minority of females should be an issue.

⁴ Approval No 107, August 2003

⁵ DLGPSR (17 March 2005) "Approved On-site Sewage Treatment Systems".



A number of different forms of composting toilets are available. The most appropriate form will depend on DN's vision for the site. At the time this report was prepared, finalised layout plans for the construction site were not available, and it was assumed that Maxi Rota-Loo® composting toilets would be potentially appropriate. The Maxi Rota-Loo® composting toilets are a batch-type toilet with eight removable composting chambers mounted on a rotating disk base used for commercial areas.

It is assumed that the composting toilets would be provided in centralised toilet blocks and that individual toilets were not provided for each unit. The Maxi Rota-Loo® has a relatively large capacity which can service 25 permanent residents.

If the Maxi Rota-Loos® are constructed with 2 pedestals and a couple of urinals, the unit could be expected to service 40 people. This increases the cost effectiveness of the composting toilets. Fibreglass pedestals are recommended for the remote location as they are more robust.

The Maxi 2000's are constructed above ground and there should be 1.3m clearance from the ground to the structure above to facilitate maintenance. Each chamber of the Maxi 2000 normally last for 6-8 weeks use before you rotate it to the next one. By the time you get around to the first chamber again it should be about 10 months after its initial use. The compost in the chambers will be about a third of the initial volume and will be pathogen free. The wastes from composting toilets are typically buried under 8 inches of dirt⁶.

Alternatively, the Biolet 200 module is a much smaller unit which can be accommodated into individual residences. This form of composting toilet would not be very cost-effective for the site as they typically cost \$3200 each, and it is considered more economical to construct toilet blocks using the Maxi 2000 model.

4.6 Summary of Wastewater Treatment Options

Table 5 summarises the wastewater treatment options considered for the different source scenarios, and Table 6 summarises the design effluent flows and qualities.

Table 5 Wastewater Treatment Options

Option	Permanent	Temporary
1A	MBR / package plant	MBR / package plant
1B	Biolytix STP	Biolytix STP and/or Biolytix BF6 filters
1C	MBR / package plant/ Biolytix STP	Composting toilets + greywater recycling (with greywater treatment from either the Biolytix or MBR/ activated sludge package plant.

⁶ From conversation with the supplier, July 2006.



Table 6 Summary of Design Effluent Flows and Qualities

	Flow (kL)	MBR		Activated Sludge Package Plant		Biolytix	
		TN (mg/L)	TP (mg/L)	TN (mg/L)	TP (mg/L)	TN (mg/L)	TP (mg/L)
Temporary	100.8	11	2	11	2	37	8
Permanent	4.18	11	2	11	2	60	11
Temporary - composting toilets option	77	11	2	11	2	35	8



5. Separate Irrigation System Requirements

5.1 Overview

MEDLI (Model for Effluent Disposal Using Land Irrigation) was used to determine the feasibility of each treatment systems and the associated land required to dispose of 100% of average dry weather flows (ADWF).

This section outlines:

- » The proposed irrigation areas;
- » The results of the water and nutrient balances; and
- » The proposed storage volumes.

5.2 Recycled Water System

Infrastructure required for the Recycled Water System include:

- » A treatment system for the wastewater;
- » A wet weather storage reservoir;
- » Wastewater reticulation (ie pipelines to collect wastewater);
- » Recycled Water reticulation (ie pumps and polyethylene pipelines to distribute and irrigate the treated wastewater).

It is expected that the relatively short lengths of pipeline and the use of materials such as polyethylene will minimise any inflow and infiltration⁷ into the recycled water system. Due to the anticipated reduced inflow and infiltration, the costs for the MBR were derived on the basis of 2 x ADWF (rather than the factor of 5 which is normally adopted for more conventional sewerage collection networks).

5.3 Wet Weather Storage Sizing

Daily climate data (from 1957 until 2005) was analysed to determine how many days of wet weather storage would be appropriate. It should be noted that the climate in the area is dry, with only 572 mm per year.

97.2% of rainfall events greater than 2 mm are 4 days or less.

⁷ Inflow and infiltration are terms that refer to stormwater that enters the sewerage reticulation either through crack or joints in pipelines and manholes (after rainfall) or through illegal connections of stormwater pipelines. Sewerage networks with high inflow and infiltration are inherently less efficient than those that limit the influx of stormwater.



Table 7 Proposed Wet Weather Storage Volumes

	4 days Storage	Proposed Storage
Temporary Facility	400 kL	400 kL
Permanent Facility	17 kL	23 kL
Temporary Facility with Composting Toilets	300 kL	300 kL

Considering that the temporary facilities are only intended to be operational for two years, the likelihood of exceedance does not appear significant. It is proposed that the storage volume for the permanent facility is increased to 23 kL (which is a standard industrial tank size) to provide an additional factor of safety.

5.4 Nutrient Balance and Irrigation Area Sizing

MEDLI was used to iteratively determine an irrigation area, which would achieve balance with respect to hydraulic and nutrient loadings. The input data into the MEDLI model for each of the different scenarios is summarised in Appendix D.

The irrigation area was modelled on the basis of using kikuyu grass. Kikuyu grass was chosen as it has a relatively high rate uptake rate of nutrients for a grass.

The determination of the irrigation area was an iterative process, which started by considering the volume of recycled water to be irrigated and a practicable irrigation rate (5mm/day). The area was then adjusted so that the transpiration rate (ie the amount of water taken up by the vegetation) was at least within 10% of the irrigation rate and an approximate water balance was achieved over the site. The required irrigation area was adjusted further (where necessary) based on the performance (ie export of nutrients) over the irrigation area.

Table 8 Summary of MEDLI results

Treatment Technology	MBR	Biolytix	MBR	Biolytix	MBR	Biolytix
Scenario	permanent	permanent	temporary	temporary	temporary with composting toilets	temporary with composting toilets
Flow (ML/day)	0.10080	0.10080	0.00418	0.00418	0.07700	0.07700
Land available (ha)	2.5	3.5	0.11	0.25	1.8	4
Storage volume (ML)	0.40	0.40	0.017	0.017	0.31	0.31
TN Effluent	11	38	11	60	11	35
TP Effluent	2	8	2	11	2	8
% reuse	100%	100%	100%	100%	100%	100%



Treatment Technology	MBR	Biolytix	MBR	Biolytix	MBR	Biolytix
Scenario	permanent	permanent	temporary	temporary	temporary with composting toilets	temporary with composting toilets
N added in irrigation	134.1	330.5	116	278.3	130.4	186.7
N removed crop (kg/ha/yr)	169.1	365	151.1	312.4	165.4	221.3
P added irrigation (kg/ha/yr)	29.4	84.1	27.9	67.4	31.2	56.2
P removed crop (kg/ha/yr)	32	60.3	25.9	53.6	29	43.3
Change in adsorbed P	-2.9	23.8	1.9	13.8	2.1	12.9
Leached PO4-P (kg/ha/yr)		0.1	0.1	0	0.1	0

The MEDLI analyses showed the following:

- » The irrigation land required is nutrient limited (ie the consideration of a sustainable rate of application of nutrients is more limiting than the consideration of application of water). This is generally the case with sustainable irrigation of recycled water and is particularly expected in dry climates.
- » The land required to irrigate recycled water treated by an MBR or activated sludge packing plant is substantially less than that required for Biolytix. The lower concentration in the effluent from an MBR reduces the nutrient export risk and enables a smaller irrigation area.
- » The assimilation rate of kikuyu for nitrogen is higher than the rate supplied by irrigation of the recycled water for all scenarios.
- » Kikuyu is not predicted to assimilate all of the phosphorus applied through irrigation, except for the permanent MBR scenario. For the other scenarios, only minor amounts of phosphorus were leached (i.e. 0.1 kg/ha/yr or less) and the majority was adsorbed in to the soil profile.

Please note that a sensitivity analyses was completed for the soil type Clayey Sand, which is a non standard MEDLI soil (refer to Section 2.2). The sensitivity test considered the standard ‘Grey Clay’ soil type and ‘Sand’. The scenario analysed effluent from a Biolytix system (as this has the highest level of nutrients so should have the greatest level of modelling variability), considering wastewater sourced from the temporary accommodation.

The results of the soil sensitivity analyses are presented in Table 9. Clays have lower permeabilities and greater phosphorus adsorbing capabilities than sand, so predictably even less leaching is predicted to occur if the soil exhibits more clay-like properties. Even if this soil is sand, the majority of the difference between the phosphorus applied and that taken up by the plant is adsorbed.



Table 9 Soil Sensitivity Analyses

Treatment Technology	Biolytix	Biolytix	Biolytix
Flow (ML/day)	0.10080	0.10080	0.10080
Land available (ha)	3.5	3.5	3.5
Soil	Clayey sand	Sand	Grey clay
N added in irrigation	330.5	330.5	330.5
N removed crop (kg/ha/yr)	365	361	393.5
Leached NO ₃ -N (kg/ha/yr)	1	1.4	0.1
P added irrigation (kg/ha/yr)	84.1	84.1	84
P removed crop (kg/ha/yr)	60.3	60.6	62.5
Change in adsorbed P	23.8	23.1	21.4
Leached PO ₄ -P (kg/ha/yr)	0.1	0.4	0



6. Combined Irrigation System Requirements

6.1 Overview

GHD were asked to investigate the feasibility of having a combined irrigation system, which would irrigate recycled water from both the temporary and permanent sources, including the discharge from the ammonium nitrate processes.

The ammonium nitrate plant will require construction before it can produce any flows. Therefore there may be an opportunity to use the irrigation area which was constructed for the temporary accommodation plant to irrigate some of the wastewater from the ammonium nitrate plant. If feasible, this solution could utilise the existing irrigation infrastructure, maintaining the vegetation and decreasing the size of the evaporation pond required. The irrigation area could be enlarged to further minimise the evaporation pond size.

Flow quantity and quality data from DN was used in a MEDLI analysis to determine the feasibility of a combined irrigation system.

6.2 Wastewater Characteristics

Wastewater from operation of the ammonium nitrate plant is estimated to be a relatively constant flow of 15m³/hr, or 130 ML/annum.⁸

DN has confirmed that the most appropriate nutrient concentration to characterise the wastewater from the plant is 1923 mg/L and 1.38 mg/L for nitrogen and phosphorus respectively.⁹ This data is based on the concentrations from the first evaporation pond at Moura.

The nitrogen level in the plant's wastewater is far in excess of the concentrations in recycled water typically irrigated. While there will be some dilution from the domestic wastewater produced from the permanent facilities, this is not likely to have a significant dilution effect (the quantity of domestic wastewater expected from the permanent facility is only 1.5 ML/year, and therefore just 1% of the flows expected from the ammonium nitrate plant).

For the purposes of this analysis, concentrations of 1923 mg/L for nitrogen and 2 mg/L for phosphorus were assumed to be representative of the combined permanent sources.

6.3 MEDLI results

It is not sustainable to irrigate the wastewater from the ammonium nitrate plant. A number of iterations of the MEDLI model were run, including deficit irrigation scenarios and scenarios which irrigated a maximum of only 1 mm. In each there was a significant amount of NO₃-N leaching, i.e. at least 2770 kg/ha/yr.

It is not considered appropriate to pursue this option further.

⁸ Email correspondence from Peter Etough dated 20th June 2006.

⁹ Email correspondence from Peter Etough dated 24th July 2006.



7. Cost Estimates

7.1 Overview

The budget indicative costs presented in this section are typically developed based on the extrapolation of recent similar project pricing in Queensland, budget quotes for some equipment items, Australian Construction Handbook (Rawlinsons 2003), industry unit rates and GHD experience. Capital costs have been developed using estimated constructed costs and include 30% contingency for engineering and peripheral costs.

The budget cost estimates do not include reticulation costs (i.e. the pipelines and fittings required to transport wastewater from the wastewater source to the wastewater treatment system) as it is understood that the layout of the facility has not yet been provided and topographical data was not provided. However, they do include an allowance for irrigation costs.

The budget estimates are based on conceptual design only and are not warranted by GHD. The capital costs should be interpreted within the context of the inclusions and exclusions outlined in Section 7.3. Further design would be recommended to achieve greater accuracy for these figures.

7.2 Cost Estimates

Table 10, Table 11 and Table 12 present indicative capital costs for each option. Please note that all cost estimates included in this report are exclusive of GST.

On a small scale, such as the volumes of domestic wastewater requiring treatment at the permanent facility, MBRs are clearly not as cost effective as Biolytix units (Table 10).

Table 10 Indicative Capital Costs - Permanent Domestic Wastewater

	MBR	Biolytix
Treatment	\$416,000	\$55,000
Storages	\$8,000	\$8,000
Irrigation	\$3,500	\$5,000
TOTAL	\$427,500	\$68,000

However, as the volume of wastewater requiring treatment increases, MBRs (or activated sludge packing plants) become increasingly cost-effective. By coincidence, the volume of wastewater where MBRs are about as cost-effective as Biolytix units is approximately the volume of wastewater expected from the temporary construction accommodation. Therefore at this level of preliminary cost comparison it is not possible to distinguish between either a MBR or activated sludge package plant or a Biolytix system on the basis of capital cost to treat wastewater from the temporary construction facility.



Table 11 Indicative Capital Costs – Temporary Construction Accommodation

	MBR	Biolytix
Treatment	\$1,482,000	\$1,505,000
Storages	\$230,000	\$230,000
Irrigation	\$30,000	\$42,000
TOTAL	\$1,742,000	\$1,777,000

It appears that some savings in the wastewater management system would be plausible if the construction camp were to utilise composting toilets. The use of composting toilets decreases the treatment costs as there is a reduced volume of wastewater and it also reduces the cost of the irrigation area. This estimate for composting toilets is based on the concept of constructing toilet blocks with urinals and the provision of composting toilets to each single dwelling is likely to be prohibitively expensive. It is not certain if the provision of toilet blocks may not be consistent with DN's vision for the construction camp.

Table 12 Indicative Capital Costs – Temporary Construction Accommodation with Composting Toilets

	MBR assumed
	Capital costs
Composting toilets	\$202,800
Treatment Plant (MBR)	\$1,287,000
Storages	\$200,000
Irrigation	\$21,600
TOTAL	\$1,711,400

At this stage, the responsibility for maintenance and operation of the treatment plant would be that of the developer, or a legal entity nominated by the developer (body corporate or similar).



7.3 Basis of Estimate – Capital Costs

7.3.1 Storages

The estimate for storage includes supply and delivery of tanks and fittings but does not include for construction of foundations. The estimate assumes the tanks are constructed above the ground on favourable ground conditions.

7.3.2 MBR Treatment

The following are included in the cost estimate for the MBR:

- » Supply and fabrication of MBR tank, anoxic tank, walkways and handrails;
- » Supply, clearance and installation of MBR modules;
- » Supply of 3 mm screen, blowers, pumps, chemical dosing systems and mixers;
- » Supply and installation of electrical equipment, MCC, PLC controller and operator interface plus cabling;
- » Supply and installation of 20 m³ fibre glass permeate tank;
- » Supply of valves, instrumentation and pipework;
- » Provision of a UV system for disinfection (assumed this will be located after the recycled water tank);
- » Civil costs for concrete slab for tanks plus control/blower building; and
- » Provision of design, drafting, administration, commissioning and testing.

The cost estimate assumes favourable ground conditions and does not include costs for:

- » Additional treatment and disposal of sludge;
- » Separation of construction into 3 stages;
- » Roads; and
- » As-constructed drawings.

It is assumed that ground conditions are favourable, and no provision has been made for acid-sulphate soils, excavation in rock, naturally soft material, or for high water tables.

7.3.3 Biolytix

The costs for the Biolytix treatment systems are based on costs supplied by the supplier, with some allowances made for construction and contingencies. The Biolytix treatment units will require excavation and it is assumed that ground conditions are favourable, with no provision made for acid-sulphate soils, excavation in rock, naturally soft material, or for high water tables.



7.3.4 Composting Toilets

In costing the compost toilet facilities, it is assumed that 15 units consisting of one Maxi Rota Loo 2000 and two urinals are supplied and constructed.

The capital cost estimate does not include costs for:

- » Construction of the toilet block building with 1.3 m clearance to the composting units;
- » Provision of toilet pedestals (to make this option comparable with other options where toilet pedestals were also not included in costs).
- » Disposal/reuse/transport of the compost material produced on site;
- » Supplementary heating for the compost; and
- » Roads.

7.3.5 Irrigation System

The irrigation system costs are based on the irrigation areas determined from the MEDLI analyses. The indicative costs consider subsurface irrigation, with laterals spaced 0.4 to 0.5m apart. The indicative costs do not include signage, earthworks, ground preparation, or any costs associated with seeding grass or supplying turf. The costs assume that ground conditions are favourable.



8. Discussion of Relative Merits

8.1 Overview

As the costs for the treatment of the wastewater from the temporary accommodation facility are comparable, the selection of the appropriate sewerage system will be heavily influenced by the preferences and perceptions of the developer and will depend on DN's vision for the development. Table 13 lists relative advantages and disadvantages of the different options.



Table 13 Advantages and Disadvantages of Each Option

Treatment process	Advantages	Disadvantages
MBR or activated sludge	<p>Treats water to a very high standard, and removes significant proportion of nutrients. This reduces the size of the irrigation area required.</p> <p>Because of the very high quality of the water, garden irrigation could also use surface irrigation, which is easier to maintain.</p>	<p>A MBR treatment plant would require specialist labour to monitor the treatment plant and to chemically dose. Sourcing this specialist labour has practical implications for the site.</p> <p>Comparatively high operational costs, estimated at \$40,000 for the permanent facility, and \$76,000 for the temporary facility.¹⁰</p> <p>Separate sludge treatment required.</p>
Biolytix units.	<p>Biological system which will not require chemical dosing.</p> <p>If there were system failure it would be less likely to affect the whole camp.</p> <p>Modular units which can easily accommodate staging of the development.</p> <p>Less risk with maintenance - maintenance costs can easily be outsourced through Biolytix as part of a long-term service agreement.</p>	<p>Relatively high nutrient loading requires larger irrigation area.</p> <p>Garden irrigation must be subsurface.</p> <p>Irrigation from the Biolytix systems is more nutrient limited than from the MBRs and a much greater area was required. This decreases the water availability to the grass and it is predicted that the grass will show some signs of water stress. Grass irrigated from the MBR is expected to look greener.</p>

¹⁰ Operational costs for the MBR include power; chemicals/cleaning agents; sludge transport and disposal; maintenance (civil structures, mechanical and electrical); membrane replacement; laboratory analysis; and operator input and labour.



Treatment process	Advantages	Disadvantages
Composting toilets	<p>The use of composting toilets reduces the quantity of effluent that needs disposal. This in turn reduces the area required for disposal, and reduces the size and cost implications of the temporary facilities which will become redundant after construction has stopped.</p> <p>Reduces the water requirements for the site.</p> <p>Biosolids from the composting toilets could be used as fertiliser on site.</p> <p>Composting toilets are very robust to changing loads. Expected to be the most robust system to population fluctuations.</p>	<p>Would require construction of toilet blocks to be cost-effective. Costs of individual composting toilets for each unit would be prohibitive.</p>



9. Conclusion and Recommendation

9.1 Conclusion

GHD were commissioned to complete a desk-top assessment of the viability of different wastewater systems for a proposed ammonium nitrate plant at Moranbah. GHD understand that the proposed works will include an ammonium nitrate plant, emulsion plant, raw water reservoir, power generation facility and evaporation pond. This investigation considers the treatment and irrigation of **domestic** wastewater (namely wastewater sourced from toilets, laundry, basins, showers, kitchen facilities) from the permanent staff at the facility, and the temporary accommodation units of construction staff. It does not consider either the treatment of wastewater from the ammonium nitrate plant or the design of the associated evaporation pond.

The conclusions from this report are:

- » Wastewater sourced from either the temporary accommodation camp or the permanent domestic facility can be treated by either a MBR, activated sludge package plant or Biolytix unit and sustainably irrigated on site.
- » Lower irrigation areas are possible with the MBR (or activated sludge package plant) because of the reduced nutrient loads in the effluent.
- » Wastewater from the ammonium nitrate plant cannot be sustainably irrigated, at least without further treatment or dilution. Further treatment would require consideration of carbon and phosphorus supply and is outside the scope of this study.
- » Biolytix units are the most cost-effective option for domestic wastewater from the permanent facility.
- » Biolytix units, MBRs and activated sludge package plants have comparable capitals costs for the temporary accommodation.
- » The use of composting toilets may reduce wastewater management costs for the temporary facility, but would require the construction of toilet blocks to be cost-effective.

9.2 Recommendations

GHD recommend that the way forward have the following steps:

- » That a lot layout is consolidated, and that DN consider their treatment option preferences.
- » It is preferable that some additional data is collected to characterise the geology on site (preferably constant head permeability tests and laboratory tests to characterise the chemical properties of the soil). The soil sensitivity tests completed in this analysis demonstrated that a sustainable system is achievable, but collecting the geological data and checking the irrigation system design will ensure that the system operates in an efficient, sustainable fashion.



- » Complete a topographical survey of the site.
- » Develop a concept design.
- » Commission a suitably qualified quantity surveyor to prepare a cost estimate for a Biolytix system, an activated sludge package plant and a MBR.

All of the above should take into account that the ultimate design will be subject to the requirements of Council and other regulatory agencies such as the Environmental Protection Agency (EPA).



Appendix A
Borehole Logs

Engineering Log - Borehole

Client: **Technip Oceania Pty Ltd**
Principal: **Dyno Knobel**
Project: **Ammonium Nitrate Plant, Moranbah**
Borehole Location: **Refer Figure 1**

Date started: **5.5.2006**

Date completed: **6.5.2006**

Logged by: **CP**

Checked by:



drill model and mounting: **EDSON Truck Mounted** slope: **-90°** R.L. Surface:
hole diameter: **100** bearing: datum:

drilling information				material substance								
method	penetration	support	notes samples, tests, etc	RL	depth metres	graphic log	classification symbol	material	moisture condition	consistency/density index	hand penetrometer	structure and additional observations
1 2 3								soil type: plasticity or particle characteristics, colour, secondary and minor components.			100 200 300 400	
WB		C			1		SC	CLAYEY SAND: Fine to medium grained sand, brown and pale orange with 10 - 20% low plasticity clay fines.	M	VD		ALLUVIAL?
			SPT 12,18,22 N*=40		2							
			SPT 21,R N*=R		3		SC	CLAYEY SAND: Fine to medium grained sand, pale orange, red and pale grey with 10 - 20% low plasticity clay fines.				SPT: R = 25 blows / 95mm
			SPT 27,R N*=R		4		CH	CLAY: High plasticity, pale grey.				SPT: R = 25 blows / 75mm XW(?) Mudstone
			SPT R N*=R		5							
			SPT R N*=R		6		SC	CLAYEY SAND: Fine to coarse grained sand, pale grey with 15 - 25% medium plasticity clay fines.				SPT: R = 30 blows / 100mm
			SPT R N*=R		7							
			SPT R N*=R		8							
			SPT R N*=R		9							
			SPT R N*=R		10							

PRELIMINARY

method AS auger screwing* AD auger drilling* RR roller/tricone W washbore CT cable tool HA hand auger DT distube B blank bit V V bit T TC bit *bit shown by suffix e.g. ADT	support T timbering N nil C casing penetration 1 2 3 4 no resistance ranging to refusal water 10/1/5-B water level on date shown water inflow water outflow	notes, samples, tests U ₂₀ undisturbed sample 50mm diameter D disturbed sample N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone V vane shear (kPa) P pressure meter B _s bulk sample R refusal	classification symbols and soil description based on unified classification system moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency/density index VS very soft S soft F firm St stiff VS _t very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
---	--	---	---	---

Revision A

BOREHOLE P07342-02.GPJ COFFEY GDT 23.06.06

Engineering Log - Borehole

Client: **Technip Oceania Pty Ltd**
Principal: **Dyno Knobel**
Project: **Ammonium Nitrate Plant, Moranbah**
Borehole Location: **Refer Figure 1**

Date started: **5.5.2006**
Date completed: **6.5.2006**
Logged by: **CP**
Checked by:



drill model and mounting: **EDSON Trucl. Mounted** slope: **-90°** R.L. Surface:
hole diameter: **100** bearing: datum:

drilling information				material substance										
method	penetration	support	water	notes samples, tests, etc	RL	depth metres	graphic log	classification symbol	material	moisture condition	consistency/density index	hand penetrometer	structure and additional observations	
	1 2 3								soil type: plasticity or particle characteristics, colour, secondary and minor components.			100 200 300 400 KPa		
				SPT R N*=R		11		SC	CLAYEY SAND: Fine to coarse grained sand, pale grey with 15 - 25% medium plasticity clay fines. (continued)	M	VD		SPT: R = 25 blows / 75mm	
				SPT R N*=R		12								
				SPT R N*=R		13								SPT: R = 25 blows / 50mm Basalt Layer
				SPT R N*=R		14								
				SPT R N*=R		15								
				SPT R N*=R		16								SPT: R = 25 blows / 80mm
				SPT R N*=R		17								
				SPT R N*=R		18		CH	GRAVELLY CLAY: High plasticity, red and brown with some fine to medium grained gravel.				SPT: R = 25 blows / 75mm Basalt Layer	
						19								
						20								

PRELIMINARY

BOREHOLE P07342-02.GPJ COFFEY.GDT 23.06.06

method AS auger screwing* AD auger drilling* RR roller/tricone W washbore CT cable tool HA hand auger DT dialtube B blank bit V V bit T TC bit *bit shown by suffix e.g. ADT	support T timbering N nil C casing penetration 1 2 3 4 no resistance ranging to refusal water 10/15/8 water level on dare shown water inflow water outflow	notes, samples, tests U _u undisturbed sample 50mm diameter D disturbed sample N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone V vane shear (kPa) P pressure meter Bs bulk sample R refusal	classification symbols and soil description based on unified classification system moisture D dry M moist W wcl Wp plastic limit Wl liquid limit	consistency/density index VS very soft S soft F firm St stiff VS: very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
--	--	--	---	---

Revision A

Engineering Log - Borehole

Client: **Technip Oceania Pty Ltd**
Principal: **Dyno Nobel**
Project: **Ammonium Nitrate Plant, Moranbah**
Borehole Location: **Refer Figure 1**

Date started: **5.5.2006**
Date completed: **6.5.2006**
Logged by: **CP**
Checked by:



drill model and mounting: EDSON Truck Mounted		slope: -90°		R.L. Surface:							
hole diameter: 100		bearing:		datum:							
drilling information				material substance							
method	penetration 1 2 3	support water	notes samples, tests, etc	depth metres	graphic log	classification symbol	material soil type: plasticity or particle characteristics, colour, secondary and minor components.	moisture condition	consistency/ density index	hand penetro- meter kPa	structure and additional observations
				21		CH	GRAVELLY CLAY: High plasticity, red and brown with some fine to medium grained gravel. (continued)	M	VD		
				22			ROCK MATERIAL - NOT YET LOGGED				Drill bit blocking, coring started
				23							
				24							
				25							
				26							
				27			Borehole BHA1 terminated at 26m				
				28							
				29							
				30							
method AS auger screwing* AD auger drilling* RR roller/tricone W washbore CT cable tool HA hand auger DT dial tube B blank bit V V bit Y TC bit *bit shown by suffix e.g. ADT		support T timbering N nil C casing penetration 1 2 3 4 no resistance ranging to refusal water 10/1/58 water level on date shown water inflow water outflow		notes, samples, tests U ₅₀ undisturbed sample 50mm diameter D disturbed sample N standard penetration test (SPT) N+ SPT - sample recovered Nc SPT with solid cone V vane shear (kPa) P pressure meter Bs bulk sample R refusal		classification symbols and soil description based on unified classification system moisture D dry M moist W wet Wp plastic limit Wl liquid limit		consistency/density index VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense			

PRELIMINARY

BOREHOLE P07342-02.GPJ COFFEY.GDT 23.06.06

Revision A

Engineering Log - Borehole

Client: **Technip Oceania Pty Ltd**
Principal: **Dyno Knobel**
Project: **Ammonium Nitrate Plant, Moranbah**
Borehole Location: **Refer Figure 1**

Date started: **7.5.2006**

Date completed: **7.5.2006**

Logged by: **CP**

Checked by:



drill model and mounting: **EDSON Truck Mounted** slope: **-90°** R.L. Surface:
hole diameter: **100** bearing: datum:

drilling information				material substance			
method	penetration	support	notes samples, tests, etc	depth metres	classification symbol	material	structure and additional observations
1 2 3				RL		soil type: plasticity or particle characteristics, colour, secondary and minor components.	
WB		C	SPT 16,29,29 N*=58	1	SW	GRAVELLY SAND: Fine to coarse grained sand, pale brown and pale grey with 10 - 20% fine to coarse grained gravel and some medium plasticity clay fines.	ALLUVIAL?
			SPT 20,R N*=R	3		PRELIMINARY	SPT: R = 33 blows / 150mm
			SPT 8,16,24 N*=40	5	SC	CLAYEY SAND: Fine to coarse grained sand, red and pale grey with 10 - 30% medium to high plasticity clay fines.	
			SPT 16,R N*=R	6	SP	SILTY SAND: Fine grained sand, red with 10 - 20% low plasticity silt fines.	SPT: R = 30 blows / 95mm XW Sandstone and with XW Ironstone seams?
			SPT R N*=R	7	SP	SAND: Fine to coarse grained, orange and pale grey with some medium plasticity clay fines.	SPT: R = 30 blows / 115mm
			SPT R N*=R	9	SP	GRAVELLY SAND: Fine to coarse grained sand, brown with 20 - 30% fine to coarse grained gravel.	SPT Bouncing, R = 25 blows / 90mm

method AS auger screwing* AD auger drilling* RR roller/cone W washbore CT cable tool HA hand auger DT diatube B blank bit V V bit T TC bit *bit shown by suffix e.g. ADT	support T timbering N nil C casing penetration 1 2 3 4 no resistance ringing to refusal water 10/1A/B water level on date shown water inflow water outflow	notes, samples, tests U ₅₀ undisturbed sample 50mm diameter D disturbed sample N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone V vane shear (kPa) P pressure meter Bs bulk sample R refusal	classification symbols and soil description based on unified classification system moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency/density index VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
--	--	---	---	---

BOREHOLE P07342-02.GPJ COFFEY.GDT 23.06.06

Revision A

Engineering Log - Borehole

Client: **Technip Oceania Pty Ltd**
Principal: **Dyno Knobel**
Project: **Ammonium Nitrate Plant, Moranbah**
Borehole Location: **Refer Figure 1**

Date started: **7.5.2006**

Date completed: **7.5.2006**

Logged by: **CP**

Checked by:



drill model and mounting: EDSON Truck Mounted slope: -90° R.L. Surface:
hole diameter: 100 bearing: datum:

drilling information				material substance										
method	penetration	support	water	notes samples, tests, etc	RL	depth metres	graphic log	classification symbol	material	moisture condition	consistency/density index	hand penetrometer	structure and additional observations	
1	2	3							soil type: plasticity or particle characteristics, colour, secondary and minor components.			10 20 30 40		
WB				SPT R N*=R		11		SP	SAND: Fine to coarse grained sand, pale orange and white with some low plasticity clay fines.		VD		SPT: R = 25 blows / 80mm XW Sandstone	
				SPT R N*=R		12		CH	CLAY: High plasticity, pale grey.				SPT: R = 25 blows / 65mm	
						13			ROCK MATERIAL - NOT YET LOGGED				Drill rig loaded to 1000kPa - drilling progressing slowly. Coring Started	
						14			PRELIMINARY					
						15								
						16								
						16				Borehole BHA3 terminated at 16m				
						17								
						18								
						19								
						20								

method AS auger screwing* AD auger drilling* RR roller/tricone W washbore CT cable tool HA hand auger DT diatube B blank bit V V bit T TC bit *bit shown by suffix e.g. ADY	support T timbering C casing penetration 1 2 3 4 no resistance ranging to refusal water 10/1/96 water level on date shown water inflow water outflow	notes, samples, tests U ₅₀ undisturbed sample 50mm diameter D disturbed sample N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone V vane shear (kPa) P pressure meter Bs bulk sample R refusal	classification symbols and soil description based on unified classification system moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency/density index VS very soft S soft F firm St stiff VS1 very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
---	--	---	---	---

BOREHOLE: P07342-02.GPJ COFFEY.GDT 23.06.06

Revision A



Engineering Log - Borehole

Client: **Technip Oceania Pty Ltd**
 Principal: **Dyno Knobel**
 Project: **Ammonium Nitrate Plant, Moranbah**
 Borehole Location: **Refer Figure 1**

drill model and mounting: **EDSON Truck Mounted** slope: **-90°** R.L. Surface:
 hole diameter: **100** bearing: datum:

drilling information				material substance				
method	penetration	support	notes samples, tests, etc	depth metres	classification symbol	material	structure and additional observations	
1 2 3				RL		soil type: plasticity or particle characteristics, colour, secondary and minor components.		
WB		C			SC	GRAVELLY CLAYEY SAND: Fine to coarse grained sand, brown with orange and red, with 20 - 30% medium plasticity clay fines and some fine to coarse grained gravel.		
			SPT 19,26,27 N*=53	1		PRELIMINARY		
			SPT 20,R N*=55	2				
			SPT R N*=R	3	SC		CLAYEY SAND: Fine to coarse grained sand, pale orange, brown and pale grey with 20 - 30% medium plasticity clay fines and some fine to medium gravel.	
			SPT R N*=R	4				
			SPT 33,R N*=R	5	SC		CLAYEY SAND: Fine to coarse grained sand, orange, brown and pale grey with 20 - 30% medium plasticity clay fines and some fine to medium gravel.	
			SPT R N*=R	6	CH		SANDY CLAY: High plasticity, pale grey with 25 - 35% fine grained sand and a trace of fine to medium grained gravel.	
			SPT R N*=R	7				
			SPT R N*=R	8				
			SPT R N*=R	9	CH		GRAVELLY SANDY CLAY: High plasticity, purple and black with 20 - 30% fine to medium grained sand and some fine to medium grained gravel.	
			SPT R N*=R	10				

method AS auger screwing* AD auger drilling* RR roller/tricone W washbore CT cable tool HA hand auger DT dialube B blank bit V V bit T TC bit *bit shown by suffix e.g. ADT	support T timbering N nil C casing penetration 1 2 3 4 no resistance ranging to refusal water 10/1/95 water level on data shown water inflow water outflow	notes, samples, tests U ₅₀ undisturbed sample 50mm diameter D disturbed sample N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone V vane shear (kPa) P pressure meter Bs bulk sample R refusal	classification symbols and soil description based on unified classification system moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency/density index VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
--	--	---	--	---

BOREHOLE P07342-02.GPJ COFFEY GDT 23.06.06

Revision A

Engineering Log - Borehole

Client: **Technip Oceania Pty Ltd**
Principal: **Dyno Knobel**
Project: **Ammonium Nitrate Plant, Moranbah**
Borehole Location: **Refer Figure 1**

Date started: **13.5.2006**
Date completed: **14.5.2006**
Logged by: **CP**
Checked by:



drill model and mounting: **EDSON Truck Mounted** slope: **-90°** R.L. Surface:
hole diameter: **100** bearing: datum:

drilling information				material substance							
method	penetration	support	notes samples, tests, etc	depth metres	graphic log	classification symbol	material	moisture condition	consistency/density index	hand penetrometer	structure and additional observations
1 2 3				RL			soil type; plasticity or particle characteristics, colour, secondary and minor components.			0-100 20-300 300-400	
			SPT R N*=R	11		CH	GRAVELLY SANDY CLAY: High plasticity, purple and black with 20 - 30% fine to medium grained sand and some fine to medium grained gravel. <i>(continued)</i>		VD		
			SPT R N*=R	12		CH	SANDY GRAVELLY CLAY: High plasticity, pale grey with 25 - 35% fine to coarse grained gravel and 15 - 20% fine to coarse grained sand.				
PRELIMINARY											
			SPT R N*=R	15		SC	CLAYEY SAND: Fine grained sand, pale grey with 30 - 40% high plasticity clay fines.				
				16							
				17							
				18							
				19							
				20							

method AS auger screwing* AD auger drilling* RR roller/tricone W washbore CT cable tool HA hand auger DT dialtube B blank bit V V bit T TC bit *bit shown by suffix e.g. ADT	support T timbering N nil C casing penetration 1 2 3 4 no resistance ranging to refusal water 10/1/5/8 water level on diae shown water inflow water outflow	notes, samples, tests U _u undisturbed sample 50mm diameter D disturbed sample N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone V vane shear (kPa) P pressure meter B _s bulk sample R refusal	classification symbols and soil description based on unified classification system moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency/density index VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
--	---	---	---	---

Revision A



Engineering Log - Borehole

Client: **Technip Oceania Pty Ltd**
 Principal: **Dyno Nobel**
 Project: **Ammonium Nitrate Plant, Moranbah**
 Borehole Location: **Refer Figure 1**

drilling information				material substance							
method	penetration	support	notes samples, tests, etc	depth metres	graphic log	classification symbol	material	moisture condition	consistency/density index	hand penetrometer	structure and additional observations
1 2 3				RL			soil type: plasticity or particle characteristics, colour, secondary and minor components.			0-200 200-300 300-400 400	
						SC	CLAYEY SAND: Fine grained sand, pale grey with 30 - 40% high plasticity clay fines. (continued)		VD		
				21		SP	SAND: Fine to coarse grained, brown.				
						CH	CLAY: High plasticity, yellow, purple and pale grey.				
							ROCK MATERIAL - NOT YET LOGGED				
				22							
				23							
				24							
				25							
				26							
				27							
							Borehole BHA5 terminated at 27m				
				28							
				29							
				30							

PRELIMINARY

BOREHOLE P07342-02.GPJ COFFEY.GDT 23.06.06

method AS auger screwing* AD auger drilling* RR roller/tricone W washbore CT cable tool HA hand auger DT diatube B blank bit V V bit T TC bit *bit shown by suffix e.g. ADT	support T timbering N nil C casing penetration 1 2 3 4 no resistance ranging to refusal water 10/178 water level on date shown water inflow water outflow	notes, samples, tests U _n undisturbed sample 50mm diameter D disturbed sample N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone V vane shear (kPa) P pressure meter Bs bulk sample R refusal	classification symbols and soil description based on unified classification system moisture O dry M moist W wet Wp plastic limit Wl liquid limit	consistency/density index VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
---	---	--	--	---

Revision A

Engineering Log - Borehole

Client: **Technip Oceania Pty Ltd**
Principal: **Dyno Nobel**
Project: **Ammonium Nitrate Plant, Moranbah**
Borehole Location: **Refer Figure 1**

Date started: **3.5.2006**
Date completed: **4.5.2006**
Logged by: **CP**
Checked by:



drill model and mounting: EDSON Truck Mounted slope: -90° R.L. Surface:
hole diameter: 100 bearing: datum:

drilling information				material substance								
method	penetration	support	notes samples, tests, etc	RL	depth metres	graphic log	classification symbol	material	moisture condition	consistency/density index	hand penetrometer	structure and additional observations
	1 2 3							soil type: plasticity or particle characteristics, colour, secondary and minor components.			100 200 300 400	
WB		C			1		SP	GRAVELLY SAND: Fine to coarse grained sand, brown with 10 - 15% fine grained gravel.		VD		
			SPT 6,19,34 N*=53		1		SP	GRAVELLY SAND: Fine to coarse grained sand, brown with 20 - 25% fine grained gravel and some low plasticity clay fines.				
			SPT 9,16,30 N*=46		2		CL	GRAVELLY CLAY: Medium plasticity, pale brown with some fine to medium grained gravel.				
					2		CL	CLAY: Medium plasticity, pale brown with some fine to medium grained gravel.				
					3							
			D		4		CH	CLAY: High plasticity, pale grey.				
					5							
			D		6							
					7							
			D		8							
					9							
					10		CH	CLAY: High plasticity, pale grey with some red mottling.				

PRELIMINARY

method AS auger screwing* AD auger drilling* RR roller/tricone W washbore CT cable tool HA hand auger DT diatube B blank bit V V bit Y TC bit *bit shown by suffix e.g. ADT	support T timbering N nil C casing penetration 1 2 3 4 10/198 water level on date shown water in flow water outflow	notes, samples, tests U ₅₀ undisturbed sample 50mm diameter D disturbed sample N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone V vane shear (kPa) P pressure meter B _s bulk sample R refusal	classification symbols and soil description based on unified classification system moisture D dry M moist W wet W _p plastic limit W _l liquid limit	consistency/density index VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
--	--	---	---	---

BOREHOLE: P07342-02.GPJ COFFEY.GDT 23.06.03

Revision A

Borehole No. **BHB1**

Sheet 2 of 2

Office Job No.: **P07342/02**

Date started: **3.5.2006**

Date completed: **4.5.2006**

Logged by: **CP**

Checked by:



Engineering Log - Borehole

Client: **Technip Oceania Pty Ltd**
 Principal: **Dyno Knobel**
 Project: **Ammonium Nitrate Plant, Moranbah**
 Borehole Location: **Refer Figure 1**

drill model and mounting: EDSON Truck Mounted slope: -90° R.L. Surface:
 hole diameter: 100 bearing: datum:

drilling information				material substance										
method	penetration	support	water	notes samples, tests, etc	RL	depth metres	graphic log	classification symbol	material	moisture condition	consistency/density index	hand penetrometer	structure and additional observations	
1 2 3									soil type: plasticity or particle characteristics, colour, secondary and minor components.			1:0 2:0 3:0 4:0		
						11		CH	CLAY: High plasticity, pale grey with some red mottling. (continued)		VD			
						12			ROCK MATERIAL - NOT YET LOGGED					
						13			PRELIMINARY					
						14								
						15				Borehole BHB1 terminated at 14.8m				
						16								
						17								
						18								
						19								
						20								

method AS auger screwing* AD auger drilling* RR roller/ricone W washbore CT cable tool HA hand auger DT dialtube B blank bit V V bit T TC bit *bit shown by suffix e.g. ADT	support T timbering C casing penetration: 1 2 3 4 no resistance ranging to refusal water 10/100 water level on date shown water inflow water outflow	notes, samples, tests U ₅₀ undisturbed sample 50mm diameter D disturbed sample N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone V vane shear (kPa) P pressure meter Bs bulk sample R refusal	classification symbols and soil description based on unified classification system moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency/density Index VS very soft S soft F firm St stiff VSt very stiff H hard Fp friable VL very loose L loose MD medium dense D dense VD very dense
--	--	---	---	---

BOREHOLE: P07342-02.GPJ COFFEY.GDI 23.06.06

Revision A



Engineering Log - Borehole

Client: **Technip Oceania Pty Ltd**
 Principal: **Dyno Knobel**
 Project: **Ammonium Nitrate Plant, Moranbah**
 Borehole Location: **Refer Figure 1**

drill model and mounting: **EDSON Tract. Mounted** slope: **-90°** R.L. Surface:
 hole diameter: **100** bearing: datum:

drilling information				material substance								
method	penetration	support	notes samples, tests, etc	depth metres	graphic log	classification symbol	material	moisture condition	consistency/density index	hand penetrometer	structure and additional observations	
	1 2 3			RL			soil type; plasticity or particle characteristics, colour, secondary and minor components.			100 200 300 400		
WB		C				CL	SANDY CLAY: Low plasticity, brown and pale grey matrix with 15 - 30% fine grained sand.		VD			
			D SPT R N*=R	1			PRELIMINARY					
				2								
			SPT R N*=R	3		SC		CLAYEY SAND: Fine to coarse grained sand, pale grey with 10 - 20% low plasticity clay fines.				
			SPT 14,R N*=R	4								
				5		CH		CLAY: High plasticity, orange, red and pale grey.				
			SPT 17,R N*=R	6		CH		CLAY: High plasticity, pale grey.				
				7								
			SPT R N*=R	8								
				9								
				10								

method AS auger screwing* AD auger drilling* RR roller/tricone W washbore CT cable tool HA hand auger DT distube B blank bit V V bit T T/C bit *bit shown by suffix e.g. ADT	support T timbering N nil C casing penetration 1 2 3 4 no resistance ranging to refusal 10/1/38 water level on date shown water inflow water outflow	notes, samples, tests U ₅₀ undisturbed sample 50mm diameter D disturbed sample N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone V vane shear (kPa) P pressure meter Bs bulk sample R refusal	classification symbols and soil description based on unified classification system moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency/density Index VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
---	--	---	---	---

BOREHOLE P07342-02.GPJ COFFEY.GDT 23.06.06

Revision A

Borehole No. **BHB3**
 Sheet 2 of 2
 Office Job No.: **P07342/02**
 Date started: **8.5.2006**
 Date completed: **8.5.2006**
 Logged by: **CP**
 Checked by:



Engineering Log - Borehole

Client: **Technip Oceania Pty Ltd**
 Principal: **Dyno Knobel**
 Project: **Ammonium Nitrate Plant, Moranbah**
 Borehole Location: **Refer Figure 1**

drill model and mounting: **EDSON Truck Mounted** slope: **-90°** R.L. Surface:
 hole diameter: **100** bearing: datum:

drilling information				material substance										
method	penetration	support	water	notes samples, tests, etc	RL	depth metres	graphic log	classification symbol	material	moisture condition	consistency/density index	hand penetrometer	structure and additional observations	
	1 2 3								soil type: plasticity or particle characteristics, colour, secondary and minor components.			100 200 300 400		
						11			ROCK MATERIAL - NOT YET LOGGED					
						12			PRELIMINARY					
						13								
						14				Borehole BHB3 terminated at 13m				
						15								
						16								
						17								
						18								
						19								
						20								

method AS auger screwing* AD auger drilling* RR roller/tricone W washbore CT cable tool HA hand auger DT diatube B blank bit V V bit T TC bit *bit shown by suffix e.g. ADT	support T (timbering N nil C casing) penetration 1 2 3 4 no resistance ranging to refusal water 10/1.98 water level on date shown water inflow water outflow 	notes, samples, tests U _u undisturbed sample 50mm diameter D disturbed sample N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone V vane shear (kPa) P pressure meter Bg bulk sample R refusal	classification symbols and soil description based on unified classification system moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency/density index VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
--	--	---	---	---

BOREHOLE P07342-02.GPJ COFFEY.GDT 23.05.06

Revision A

Engineering Log - Borehole

Client: **Technip Oceania Pty Ltd**
Principal: **Dyno Knobel**
Project: **Ammonium Nitrate Plant, Moranbah**
Borehole Location: **Refer Figure 1**

Date started: **12.5.2006**
Date completed: **12.5.2006**
Logged by: **CP**
Checked by:



drill model and mounting: **EDSON Truck Mounted** slope: **-90°** R.L. Surface:
hole diameter: **100** bearing: datum:

drilling information				material substance							
method	penetration	support	notes	depth	log	classification	material	moisture	consistency/density	hand	structure and
1 2 3		water	samples, tests, etc	metres	graphic	symbol	soil type; plasticity or particle characteristics, colour, secondary and minor components.	condition	index	penetro- kPa meter	additional observations
WB		C				SC	CLAYEY SAND: Fine to medium grained sand, brown to dark brown with 30 - 40% high plasticity clay fines.		D		
			SPT 3.5,10 N*=15	1			PRELIMINARY				
				2							
			SPT R N*=R	3		GP		CLAYEY SANDY GRAVEL: Fine to coarse grained gravel, brown with 10 - 20% fine to coarse sand and some low plasticity clay fines.		VD	
				4							
			SPT R N*=R	5		SC		CLAYEY SAND: Fine to coarse grained, pale orange and brown with 15 - 20% low plasticity clay fines.			
				6							
			SPT R N*=R	7		SC		CLAYEY SAND: Fine to coarse grained, pale grey, orange and red with 15 - 20% low plasticity clay fines.			
				8							
			SPT R N*=R	9		SC		GRAVELLY CLAYEY SAND: Fine to coarse grained sand, pale grey with 25 - 35% medium plasticity clay fines and some fine to coarse grained gravel.			
				10							

method AS auger screwing* AD auger drilling* RR roller/tricone W washbore CT cable tool HA hand auger DT distube B blank bit V V bit T TC bit *bit shown by suffix e.g. ADT	support T timbering N nil C casing penetration 1 2 3 4 n resistance ranging to n/300 water 10/1/98 water level on date shown water inflow water outflow	notes, samples, tests U ₅₀ undisturbed sample 50mm diameter D disturbed sample N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone V vane shear (kPa) P pressure meter Bs bulk sample R refusal	classification symbols and soil description based on unified classification system moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency/density index VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
--	--	--	---	---

BOREHOLE_P07342/02.GPJ COFFEY.GDT 23.06.06

Revision A

Engineering Log - Borehole

Client: **Technip Oceania Pty Ltd**

Date started: **12.5.2006**

Principal: **Dyno Nobel**

Date completed: **12.5.2006**

Project: **Ammonium Nitrate Plant, Moranbah**

Logged by: **CP**

Borehole Location: **Refer Figure 1**

Checked by:



drill model and mounting: EDSON Truck Mounted slope: -90° R.L. Surface:
 hole diameter: 100 bearing: datum:

drilling information				material substance								
method	penetration	support	notes	depth	graphic log	classification	material	moisture	consistency/density	hand	structure and	
	1 2 3	water	samples, tests, etc	RL metres		symbol	soil type; plasticity or particle characteristics, colour, secondary and minor components.	condition	index	penetration	additional observations	
										kPa		
										300		
										300		
										400		
			SPT R N*=R	11		CH	CLAY: High plasticity, pale grey.		VD			
			SPT R N*=R	12		SC	CLAYEY SAND: Fine to coarse grained, pale grey with 20 - 40% high plasticity clay fines.					
				13			PRELIMINARY					
			SPT R N*=R	15		CH		GRAVELLY SANDY CLAY: High plasticity, pale grey with 15 - 25% fine to coarse grained sand and 15 - 20% fine to coarse grained gravel.				
				16				ROCK MATERIAL - NOT YET LOGGED				
				17								
				18								
				19								
				20								
Borehole BHB5 terminated at 19.5m												

method AS auger screwing* AD auger drilling* RR roller/tricone W washbore CT cable tool HA hand auger DT dial tube B blank bit V V bit Y TC bit *bit shown by suffix e.g. ADT	support T timbering N nil C casing penetration 1 2 3 4 no resistance ranging to refusal water 10/1/98 water level on d/tile shown water inflow water outflow	notes, samples, tests U _{un} undisturbed sample 50mm diameter D disturbed sample N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone V vane shear (kPa) P pressure meter Bs bulk sample R refusal	classification symbols and soil description based on unified classification system moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency/density index VS very soft S soft F firm SI stiff VSI very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
--	--	--	---	---

Revision A

BOREHOLE P07342-02.GPJ COFFEY.GDI 23.08.06

Engineering Log - Borehole

Client: **Technip Oceania Pty Ltd**
Principal: **Dyno Knobel**
Project: **Ammonium Nitrate Plant, Moranbah**
Borehole Location: **Refer Figure 1**

Date started: **4.5.2006**
Date completed: **4.5.2006**
Logged by: **CP**
Checked by:



drilling information				material substance												
method	penetration			notes samples, tests, etc	RL	depth metres	graphic log	classification symbol	material <small>soil type: plasticity or particle characteristics, colour, secondary and minor components.</small>	moisture condition	consistency/density index	hand penetrometer			structure and additional observations	
	1	2	3									100 kPa	200 kPa	300 kPa		400 kPa
WB								CH	CLAY: High plasticity, pale grey with a trace of medium to coarse grained gravel.		VD					
				D		1										
				SPT R N=8		2		SC	CLAYEY SAND: Fine grained, pale grey with 25 - 35% high plasticity clay fines.							
						3										
				SPT R N=8		4		SC	CLAYEY SAND: Fine to medium grained, pale orange and red layering with 10 - 20% low plasticity clay fines.							
						5			ROCK MATERIAL - NOT YET LOGGED							
						6			PRELIMINARY							
						7										
						8										
						8				Borehole BHC1 terminated at 8m						
						9										
						10										

BOREHOLE: P07342-02.GPJ COFFEY G50T_23.06.06

method AS auger screwing* AD auger drilling* RR roller/tricone W washbore CT cable tool HA hand auger DT distube B blank bit V V bit T TC bit *bit shown by suffix e.g. ADT	support T timbering N nil C casing penetration 1 2 3 4 no resistance ranging to refusal water 10/1/98 water level on drile shown water inflow water outflow	notes, samples, tests U ₅₀ undisturbed sample 50mm diameter D disturbed sample N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone V vane shear (kPa) P pressure meter Es bulk sample R refusal	classification symbols and soil description based on unified classification system moisture D dry M moist W wet W _p plastic limit W _L liquid limit	consistency/density index VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
--	---	---	---	---

Revision A



Engineering Log - Borehole

Client: **Technip Oceania Pty Ltd**
Principal: **Dyno Knobel**
Project: **Ammonium Nitrate Plant, Moranbah**
Borehole Location: **Refer Figure 1**

drill model and mounting: **EDSON Truck Mounted** slope: **-90°** R.L. Surface:
hole diameter: **100** bearing: datum:

drilling information				material substance							
method	penetration	support	notes samples, tests, etc	depth metres	graphic log	classification symbol	material	moisture condition	consistency/density index	hand penetrometer	structure and additional observations
1 2 3				RL			soil type: plasticity or particle characteristics, colour, secondary and minor components.			100 200 300 400	
WB		C				SC	CLAYEY SAND: Fine to medium grained, pale brown and pale orange with 20 - 30% low plasticity clay fines.		VD		
			D				PRELIMINARY				
			SPT 25,R N*=R	1							
			SPT 14,22,R N*=R	2							
			SPT R N*=R	3							
			SPT R N*=R	4							
			SPT R N*=R	5							
			SPT R N*=R	6							
			SPT R N*=R	7							
			SPT R N*=R	8		CL					
			SPT R N*=R	9							
				10			SANDY CLAY: Medium plasticity, pale grey with 15 - 30% fine grained sand.				

method AS auger screwing* AD auger drilling* RR roller/tricone W washbore CT cable tool HA hand auger DT diatube B blank bit V V bit T TC bit *bit shown by suffix e.g. ADT	support T timbering N nil C casing penetration 1 2 3 4 no resistance rising to refusal water 10/1/98 water level on date shown water inflow water outflow	notes, samples, tests U ₅₀ undisturbed sample 50mm diameter D disturbed sample N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone V vane shear (KPa) P pressure meter Es bulk sample R refusal	classification symbols and soil description based on unified classification system moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency/density index VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
--	---	---	---	---

BOREHOLE_P07342-02.GPJ COFFEY.GDT 23.06.06

Revision A

Borehole No. **BHC3**

Sheet 2 of 2
Office Job No.: **P07342/02**

Engineering Log - Borehole

Client: **Technip Oceania Pty Ltd**
Principal: **Dyno Nobel**
Project: **Ammonium Nitrate Plant, Moranbah**
Borehole Location: **Refer Figure 1**

Date started: **9.5.2006**
Date completed: **10.5.2006**
Logged by: **CP**
Checked by:



drill model and mounting: EDSON Truck Mounted slope: -90° R.L. Surface:
hole diameter: 100 bearing: datum:

drilling information				material substance									
method	penetration	support	water	notes samples, tests, etc	RL	depth metres	graphic log	classification symbol	material	moisture condition	consistency/density index	hand penetrometer	structure and additional observations
1 2 3									soil type: plasticity or particle characteristics, colour, secondary and minor components.			100 200 300 400 KPa	
				SPT R N*=R		11		CL	SANDY CLAY: Medium plasticity, pale grey with 15 - 30% fine grained sand. (continued)		VD		
						12		CH	CLAY: High plasticity, red, orange and brown.				
PRELIMINARY													
				SPT R N*=R		14		CH	CLAY: High plasticity, pale grey.				
						15			ROCK MATERIAL - NOT YET LOGGED				
						16							
						17							
						18							
						19			Borehole BHC3 terminated at 18m				
						20							

method AS auger screwing* AD auger drilling* RR roller/tricone W washbore CT cable tool HA hand auger DT diatube B blank bit V V bit T TC bit *bit shown by suffix e.g. ADT	support T timbering N nil C casing penetration: no resistance ranging to refusal water 10/1/9t: water level on date shown water inflow water outflow 	notes, samples, tests U ₅₀ undisturbed sample 50mm diameter D disturbed sample N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone V vane shear (kPa) P pressure meter Bs bulk sample R refusal	classification symbols and soil description based on unified classification system moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency/density index VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
--	---	---	---	---

BOREHOLE P07342-02.GPJ COFFEY.GDT 23.06.05

Revision A

Engineering Log - Borehole

Client: **Technip Oceania Pty Ltd**
Principal: **Dyno Nobel**
Project: **Ammonium Nitrate Plant, Moranbah**
Borehole Location: **Refer Figure 1**

Date started: **12.5.2006**
Date completed: **13.5.2006**
Logged by: **CP**
Checked by:



drill model and mounting: **EDSON Trucl: Mounted** slope: **-90°** R.L. Surface:
hole diameter: **100** bearing: datum:

drilling information				material substance							
method	penetration	support	notes samples, tests, etc	depth metres	graphic log	classification symbol	material	moisture condition	consistency/density index	hand penetrometer	structure and additional observations
1 2 3				RL			soil type; plasticity or particle characteristics, colour, secondary and minor components.			30 20 10 kPa meter	
WB		C				SC	CLAYEY SAND: Fine to medium grained sand, brown with 20 - 30% low plasticity clay fines and some fine to medium grained gravel.		VD		
			SPT 10,15,26 N*=41	1			PRELIMINARY				
			SPT 15,24,35 N*=59	2		SC	CLAYEY SAND: Fine to medium grained, pale orange and brown with 20 - 30% low plasticity clay fines.				
			SPT 28,R N*=R	3		CH	SANDY CLAY: High plasticity, pale grey clay in a 25 - 35% fine to coarse grained, pale grey sand matrix.				
			SPT R N*=R	4		SC	GRAVELLY CLAYEY SAND: Fine to coarse grained, pale grey with 25 - 35% high plasticity clay fines and some medium to coarse grained gravel.				
			SPT R N*=R	5		CH	CLAY: High plasticity, pale grey.				
			SPT R N*=R	6		SC	CLAYEY SAND: Fine to medium grained, pale yellow and pale grey with 30 - 40% high plasticity clay fines.				
			SPT R N*=R	7		CH					
			SPT R N*=R	8		SC					
			SPT R N*=R	9		SC					
			SPT R N*=R	10		SC					

method AS auger screwing* AD auger drilling* RR roller/tricone W washbore CT cable tool HA hand auger D/T dilatube B blank bit V V bit T TC bit *bit shown by suffix e.g. ADT	support T timbering N nil C casing penetration 1 2 3 4 no resistance ranging to refusal water 10/1/98 water level on date shown water inflow water outflow	notes, samples, tests U _u undisturbed sample 50mm diameter D disturbed sample N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone V vane shear (kPa) P pressure meter Bs bulk sample R refusal	classification symbols and soil description based on unified classification system moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency/density index VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
--	--	---	---	---

Revision A



Engineering Log - Borehole

Client: **Technip Oceania Pty Ltd**
 Principal: **Dyno Knobel**
 Project: **Ammonium Nitrate Plant, Moranbah**
 Borehole Location: **Refer Figure 1**

drill model and mounting: EDSON Truck Mounted slope: -90° R.L. Surface:
 hole diameter: 100 bearing: datum:

drilling information				material substance									
method	penetration	support	water	notes samples, tests, etc	RL	depth metres	graphic log	classification symbol	material	moisture condition	consistency/density index	hand penetrometer	structure and additional observations
1 2 3									soil type; plasticity or particle characteristics, colour, secondary and minor components.			100 200 300 400 kPa	
				SPT R N=R		11		SC	CLAYEY SAND: Fine to coarse grained, pale grey with 20 - 30% high plasticity clay fines.		VD		
				SPT R N=R		12		CH	CLAY: High plasticity, pale grey.				
PRELIMINARY													
						15			ROCK MATERIAL - NOT YET LOGGED				
						17			Borehole BHC5 terminated at 17.5m				

method AS auger screwing* AD auger drilling* RR roller/turbine W washbore CT cable tool HA hand auger DT diatube B blank bit V V bit Y TC bit *bit shown by suffix e.g. ADY	support T timbering N nil C casing penetration 1 2 3 4 no resistance ranging to refusal water 10/1/98 water level on ditta shown water inflow water outflow	notes, samples, tests U ₅₀ undisturbed sample 50mm diameter D disturbed sample N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone V vane shear (kPa) P pressure meter Bs bulk sample R refusal	classification symbols and soil description based on unified classification system moisture O dry M moist W wet Wp plastic limit Wl liquid limit	consistency/density index VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
--	---	---	--	---

Revision A

BOREHOLE: P07342-02.GPJ COFFEY.GDI 23.05.06

Engineering Log - Borehole

Client: **Technip Oceania Pty Ltd**
Principal: **Dyno Knobel**
Project: **Ammonium Nitrate Plant, Moranbah**
Borehole Location: **Refer Figure 1**

Date started: **16.5.2006**
Date completed: **16.5.2006**
Logged by: **CP**
Checked by:



drilling information				material substance								
method	penetration	support	notes samples, tests, etc	RL	depth metres	graphic log	classification symbol	material	moisture condition	consistency/density index	hand penetrometer	structure and additional observations
1 2 3								soil type: plasticity or particle characteristics, colour, secondary and minor components.			100 200 300 400	
WB		C					CH	SANDY CLAY: High plasticity, pale grey with 15 - 20% fine grained sand.		VD		
			SPT 22,R N*=R		1			PRELIMINARY				
			SPT R N*=R		2		SC	CLAYEY SAND: Fine to coarse grained, pale grey with 20 - 30% high plasticity clay fines.				
			SPT R N*=R		3		SP	SAND: Fine to coarse grained sand, brown.				
			SPT R N*=R		4		SC	CLAYEY SAND: Fine to coarse grained, pale grey with 20 - 30% high plasticity clay fines.				
			SPT R N*=R		5		CH	CLAY: High plasticity, pale grey.				
			SPT 26,R N*=R		6							
			SPT R N*=R		7							
			SPT 29,R N*=R		8							
					9							
					10							

BOREHOLE P07342-02-SP1 COFFEY.GDT 23.06.06

method AS auger screwing* AD auger drilling* RR roller/tricone W washbore CT cable tool HA hand auger DT disturb B blank bit V V bit T TC bit *bit shown by suffix e.g. ADT	support Y timbering N nil C casing penetration 1 2 3 4 1 - no resistance 2 - resistance 3 - refusal 4 - refusal water 10/1/98 water level on date shown water inflow water outflow	notes, samples, tests U _w undisturbed sample 50mm diameter D disturbed sample N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone V vane shear (kPa) P pressure meter Bs bulk sample R refusal	classification symbols and soil description based on unified classification system moisture D dry M moist W wet W _p plastic limit W _L liquid limit	consistency/density index soil description based on unified classification system VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
--	--	---	--	---

Revision A

Engineering Log - Borehole

Client: **Technip Oceania Pty Ltd**

Principal: **Dyno Knobel**

Project: **Ammonium Nitrate Plant, Moranbah**

Borehole Location: **Refer Figure 1**



drill model and mounting: EDSON Truck Mounted		slope: -90°		R.L. Surface:										
hole diameter: 100		bearing:		datum:										
drilling information				material substance										
method	penetration 1 2 3	support water	notes samples, tests, etc	depth metres	graphic log	classification symbol	material soil type: plasticity or particle characteristics, colour, secondary and minor components.	moisture condition	consistency/ density index	hand penetration meter 100 200 300 400	structure and additional observations			
			SPT 21,R N*=R	11		CH	CLAY: High plasticity, pale grey. (continued)		VD					
			SPT 24,R N*=R	12			PRELIMINARY							
				13										
				14										
				15			ROCK MATERIAL - NOT YET LOGGED							
				16										
				17										
				18			Borehole BHD1 terminated at 17.5m							
				19										
				20										
method AS auger screwing* AD auger drilling* RR roller/tricone W washbore CT cable tool HA hand auger DT diatube B blank bit V V bit T TC bit *bit shown by suffix e.g. ADT			support T timbering N nil C casing penetration 1 2 3 4 no resistance ranging to refusal water 10/1/5/8 water level on date shown water inflow water outflow			notes, samples, tests U ₅₀ undisturbed sample 50mm diameter D disturbed sample N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone V vane shear (kPa) P pressure meter B& bulk sample R refusal			classification symbols and soil description based on unified classification system moisture D dry M moist W wet Wp plastic limit Wl liquid limit			consistency/density index VS very soft S soft F firm St stiff VS: very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense		

BOREHOLE P07342/02.GPJ COFFEY.GDT 23.06.06

Engineering Log - Borehole

Client: **Technip Oceania Pty Ltd**

Principal: **Dyno Knobel**

Project: **Ammonium Nitrate Plant, Moranbah**

Borehole Location: **Refer Figure 1**



drilling information				material substance									
method	penetration	support	notes samples, tests, etc	depth metres	graphic log	classification symbol	material	moisture condition	consistency/density index	hand penetrometer	structure and additional observations		
1 2 3				RL			soil type: plasticity or particle characteristics, colour, secondary and minor components.			no. 200 kPa			
WB		C				CL	SANDY CLAY: Low to medium plasticity, pale grey with 15 - 25% fine to medium grained sand and a trace of fine grained gravel.		VD				
			SPT 27,R N*=R	1			PRELIMINARY						
				2									
			SPT R N*=R	3		CL		SANDY GRAVELLY CLAY: Medium plasticity, pale grey and pale orange matrix with 15 - 25% coarse grained gravel and some fine to medium grained sand.					
				4		SC		CLAYEY SAND: Fine to coarse grained sand, pale grey with 20 - 30% medium plasticity clay.					
			SPT R N*=R	5									
				6									
			SPT R N*=R	7									
				8									
			SPT R N*=R	9		CH		CLAY: High plasticity, pale grey.					
				10									

BOREHOLE P07342-02.GPJ COFFEY.GDT 23.06.06

Revision A

Borehole No. **BHD3**

Engineering Log - Borehole

Sheet 2 of 2

Office Job No.: **P07342/02**

Client: **Technip Oceania Pty Ltd**

Date started: **11.5.2006**

Principal: **Dyno Knobel**

Date completed: **11.5.2006**

Project: **Ammonium Nitrate Plant, Moranbah**

Logged by: **CP**

Borehole Location: **Refer Figure 1**

Checked by:



drill model and mounting: EDSON Truck Mounted slope: -90° R.L. Surface:
 hole diameter: 100 bearing: datum:

drilling information				material substance								
method	penetration	support	water	notes samples, tests, etc	depth metres	graphic log	classification symbol	material	moisture condition	consistency/density index	hand penetrometer	structure and additional observations
1 2 3					RL			soil type: plasticity or particle characteristics, colour, secondary and minor components.			100 200 300 400 500 600 700 800 900 meter	
				SPT R N=BR	11		CH	CLAY: High plasticity, pale grey. (continued)		VD		
				SPT R N=BR	12		SC	CLAYEY SAND: Fine to coarse grained sand, pale gray with 20 - 30% low to medium plasticity clay fines.				
					13	PRELIMINARY						
				SPT R N=BR	15			ROCK MATERIAL - NOT YET LOGGED				
					16							
					17							
					18			Borehole BHD3 terminated at 17.5m				
					19							
					20							

method AS auger screwing* AD auger drilling* RR roller/tricone W washbore CT cable tool HA hand auger DT diatube B blank bit V v bit T TC bit *bit shown by suffix e.g. ADT	support T timbering N nil C casing penetration 1 2 3 4 no resistance ranging to refusal water 10/15/20 water level on date: shown water inflow water outflow	notes, samples, tests U _u undisturbed sample 50mm diameter D disturbed sample N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone V vane shear (kPa) P pressure meter Bs bulk sample R refusal	classification symbols and soil description based on unified classification system moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency/density index VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
--	--	---	---	---

BOREHOLE: P07342/02.GPJ COFFEY.GDT 23.06.06

Revision A

Engineering Log - Borehole

Client: **Technip Oceania Pty Ltd**
Principal: **Dyno Knobel**
Project: **Ammonium Nitrate Plant, Moranbah**
Borehole Location: **Refer Figure 1**

Date started: **15.5.2006**
Date completed: **16.5.2006**
Logged by: **CP**
Checked by:



drilling information				material substance										
method	penetration	support	notes samples, tests, etc	RL	depth metres	graphic log	classification symbol	material	moisture condition	consistency/density index	hardness penetrometer	structure and additional observations		
WB	1 2 3	C			1		SP	SAND: Fine to coarse grained sand, brown with some low plasticity clay fines.		VD				
			SPT 10,8,12 N*=20		2		GP	SANDY GRAVEL: Fine to coarse grained gravel, brown with 20 - 30% fine to coarse grained sand.						
			SPT R N*=R		3		SP	GRAVELLY SAND: Fine to coarse grained sand, pale grey / pale brown with 15 - 25% fine to medium grained gravel.						
			SPT R N*=R		4		SC	CLAYEY SAND: Fine to medium grained sand, pale grey and pale orange with 20 - 30% low plasticity clay fines.						
			SPT R N*=R		6		SC	CLAYEY SAND: Fine to medium grained sand, pale grey with 20 - 30% low plasticity clay fines.						
			SPT R N*=R		7		SC	CLAYEY SAND: Fine to medium grained sand, pale grey with 30 - 40% low plasticity clay fines.						
			SPT R N*=R		9									
PRELIMINARY														
method AS auger screwing* AD auger drilling* RR roller/tricone W washbore CY cable tool HA hand auger DT dlatube B blank bit V V bit T TC bit *bit shown by suffix e.g. ADT			support T timbering N nil C casing penetration 1 2 3 4 no resistance ranging to refusal water 10/1/93 water level on date shown water inflow water outflow			notes, samples, tests U ₅₀ undisturbed sample 50mm diameter D disturbed sample N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone V vane shear (kPa) P pressure meter Bs bulk sample R refusal			classification symbols and soil description based on unified classification system moisture D dry M moist W wet Wp plastic limit Wl liquid limit			consistency/density index VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense		

BOREHOLE P07342-02.GPJ COFFEY GDT 23.06.06

Revision A

Engineering Log - Borehole

Client: **Technip Oceania Pty Ltd**

Date started: **15.5.2006**

Principal: **Dyno Knobel**

Date completed: **16.5.2006**

Project: **Ammonium Nitrate Plant, Moranbah**

Logged by: **CP**

Borehole Location: **Refer Figure 1**

Checked by:



drill model and mounting:	EDSON Truck Mounted	slope:	-90°	R.L. Surface:
hole diameter:	100	bearing:		datum:

drilling information				material substance				
method	penetration	support	notes samples, tests, etc	depth metres	classification symbol	material	structure and additional observations	
123					SC	CLAYEY SAND: Fine to medium grained sand, pale grey with 30 - 40% low plasticity clay fines. (continued)		
			SPT R N*=R	11	CH	CLAY: High plasticity, pale grey.		
				12		PRELIMINARY		
				13				
			SPT R N*=R	14	SC		CLAYEY SAND: Fine to medium grained sand, pale grey with 25 - 35% high plasticity clay fines.	
				15				
				16				
				17	CH	CLAY: High plasticity, pale grey. ROCK MATERIAL - NOT YET LOGGED		
			SPT R N*=R	18				
				19				
				20				

BOREHOLE: P07342-02.GPJ COFFEY.GDT 23.06.06

method AS auger screwing* AD auger drilling* RR roller/tricone W washbore CT cable tool HA hand auger DT dilatube B blank bit V V bit T TC bit *bit shown by suffix e.g. ADT	support T timbering N nil C casing penetration 1 2 3 4 no resistance ranging to refusal water 10/1/91: water level on dat: shown water inflow water outflow	classification symbols and soil description based on unified classification system U ₂₀ undisturbed sample 50mm diameter D disturbed sample N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone V vane shear (kPa) P pressure meter Bs bulk sample R refusal	consistency/density index VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
moisture D dry M moist W wet Wp plastic limit Wl liquid limit			



Appendix B
MEDLI soil profiles

Adopted and Standard



Table 14 Standard MEDLI Profile: Sand

<u>Soil Water</u>				
Layer	1	2	3	4
Soil Layer Thickness (mm)	100	500	600	300
Air Dry (%v)	4	0.1	0.1	0.1
Lower Storage Limit (theta at 15 bar)	4	6.4	7.5	6
Drained Upper Limit (theta at 0.3 bar)	10.9	13.6	13.8	9.1
Plant Available Water Content	6.9	36	37.8	9.3
Saturated Water Content (% v/v)	50.1	42.3	43.6	43.1
Bulk Density (g/cc)	1.31	1.52	1.48	1.5
Porosity (% v/v)	50.6	42.7	44	43.5
Saturated Conductivity (mm/hr)	50	50	20	10
Runoff Curve no	70		Lag	0.73
Stage 1 drying max (mm)	10		Wet Day	0.49
Slope of Stage 2 drying (mm/day ^ 0.5)	4.5		Albedo	0.23
<u>Soil Nitrogen</u>				
Initial Nitrate N (mg/kg)	7			
Initial Organic N (mg/kg)	350			
Ammonification of Soil Organic N	0.00035			
Denitrification	0.1			
<u>Soil Phosphorus</u>				
Design depth for Soil P Storage (mm)	1500			
Layer	1	2	3	4
Initial Soil Solution P (mg/L)	0.1	0.1	0.1	0.1
Adsorption Coefficient	75	75	75	75
Adsorption Exponent	0.33	0.33	0.33	0.33
Desorption Exponent	0.15	0.15	0.15	0.15



Table 15 Standard MEDLI Profile: Grey Clay

<u>Soil Water</u>				
Layer	1	2	3	4
Soil Layer Thickness (mm)	100	500	600	300
Air Dry (%v)	4.2	0.1	0.1	0.1
Lower Storage Limit (theta at 15 bar)	26.7	27.5	30.7	32.8
Drained Upper Limit (theta at 0.3 bar)	42	43.6	42.4	42.7
Plant Available Water Content	15.3	80.5	70.2	29.7
Saturated Water Content (% v/v)	47	48.6	47.4	48.2
Bulk Density (g/cc)	1.39	1.35	1.38	1.36
Porosity (% v/v)	47.5	49.1	47.9	48.7
Saturated Conductivity (mm/hr)	10	1	0.5	0.1
Runoff Curve no	75		Lag	0.73
Stage 1 drying max (mm)	6		Wet Day	0.49
Slope of Stage 2 drying (mm/day ^ 0.5)	3.5		Albedo	0.23
<u>Soil Nitrogen</u>				
Initial Nitrate N (mg/kg)	2.5			
Initial Organic N (mg/kg)	800			
Ammonification of Soil Organic N	0.00035			
Denitrification	0.1			
<u>Soil Phosphorus</u>				
Design depth for Soil P Storage (mm)	1500			
Layer	1	2	3	4
Initial Soil Solution P (mg/L)	0.1	0.1	0.1	0.1
Adsorption Coefficient	73	73	73	73
Adsorption Exponent	0.39	0.39	0.39	0.39
Desorption Exponent	0.25	0.25	0.25	0.25



Table 16 MEDLI Soil Profile Adopted to Represent “Clayey Sand”

<u>Soil Water</u>				
Layer	1	2	3	4
Soil Layer Thickness (mm)	100	500	600	300
Air Dry (%v)	4	0.1	0.1	0.1
Lower Storage Limit (theta at 15 bar)	7	7	7	7
Drained Upper Limit (theta at 0.3 bar)	18	18	18	18
Plant Available Water Content	11	55	66	33
Saturated Water Content (% v/v)	50.1	42.3	43.6	43.1
Bulk Density (g/cc)	1.31	1.52	1.48	1.5
Porosity (% v/v)	50.6	42.6	44	43.5
Saturated Conductivity (mm/hr)	40	40	10	5
Runoff Curve no	72		Lag	0.73
Stage 1 drying max (mm)	9		Wet Day	0.49
Slope of Stage 2 drying (mm/day ^ 0.5)	4.2		Albedo	0.23
<u>Soil Nitrogen</u>				
Initial Nitrate N (mg/kg)	6			
Initial Organic N (mg/kg)	400			
Ammonification of Soil Organic N	0.00035			
Denitrification	0.1			
<u>Soil Phosphorus</u>				
Design depth for Soil P Storage (mm)	1500			
Layer	1	2	3	4
Initial Soil Solution P (mg/L)	0.1	0.1	0.1	0.1
Adsorption Coefficient	74	74	74	74
Adsorption Exponent	0.35	0.35	0.35	0.35
Desorption Exponent	0.18	0.18	0.18	0.18



Appendix C
Wastewater Design Parameters



Table 17 Design Parameters

	Permanent Staff	Temporary Staff	Temporary Staff (Composting Toilets)
EP	38	550	550
% of Suggested Flow	61	100	78
Flow per Capita (l/EP/d)	110	180	140
Total Flow (kL/d)	4.2	100	77
Peak Flow (kL/d) ¹¹	12.6	300	231
BOD Load (kg/d) ¹²	2.3	33	33
COD Load (kg/d) ¹³	2.7	38.5	38.5
TSS Load (kg/d)	5.2	75.9	75.9
TN Load (kg/d)	0.5	7.4	7.4
TP Load (kg/d)	0.09	1.3	1.3
BOD Concentration (mg/l) ¹⁴	550	330	429
COD Concentration (mg/l)	646	385	500
TSS Concentration (mg/l)	1244	759	986
TN Concentration (mg/l)	120	74	96
TP Concentration (mg/l)	21.5	13	16.9
Minimum Temperature (°C)	15	15	15
Maximum Temperature (°C)	25	25	25

¹¹ Based on a Peak to average flow of 3:1

¹² The following per capita loads were used – 60 g BOD, 70 g TSS, 13.5 g TN, 2.4 g TP

¹³ Based on a COD:BOD of 2.3:1

¹⁴ All concentrations based on average flow



Appendix D
MEDLI Input Data



Table 18 Summary of MEDLI Input Parameters – Temporary Accommodation

Category	Variable	Value
WASTE ESTIMATION	Type	“Other”
	Effluent Vol per day (ADWF)	100.8 kL/day
	TN (mg/L)	11 for MBR/Activated Sludge; 37 for Biolytix.
	TP (mg/L)	2 for MBR/Activated Sludge; 8 for Biolytix.
	Operating Period	7 days/week
CLIMATE	Site Name	Moranbah
	Latitude	22° 00' S
	Longitude	148° 05' E
	Start Date	1/1/1957
	End Date	31/12/2005
SOIL TYPE		Clayey Sand ¹⁵
STORAGE		400 kL
PLANT		Kikuyu
IRRIGATION	Area Available	Variable – to be determined
	Trigger	Once every day
	Irrigate to:	5mm

¹⁵ From borehole data from adjacent site. ‘Clayey sand’ is not a standard profile in MEDLI, so an amalgum of the standard profiles of ‘Sand’ and “Grey Clay” were used.



Table 19 Summary of MEDLI Input Parameters – Permanent Facilities

Category	Variable	Value
WASTE ESTIMATION	Type	“Other”
	Effluent Vol per day (ADWF)	4.2 kL/day
	TN (mg/L)	11 for MBR/Activated Sludge; 60 for Biolytix.
	TP (mg/L)	2 for MBR/Activated Sludge; 11 for Biolytix.
	Operating Period	7 days/week
CLIMATE	Site Name	Moranbah
	Latitude	22° 00' S
	Longitude	148° 05' E
	Start Date	1/1/1957
	End Date	31/12/2005
SOIL TYPE		Clayey Sand ¹⁶
STORAGE		17 kL
PLANT		Kikuyu
IRRIGATION	Area Available	Variable – to be determined
	Trigger	Once every day
	Irrigate to:	5mm

¹⁶ From borehole data from adjacent site. ‘Clayey sand’ is not a standard profile in MEDLI, so an amalgum of the standard profiles of ‘Sand’ and “Grey Clay” were used.



Table 20 Summary of MEDLI Input Parameters – Temporary Accommodation with Composting Toilets

Category	Variable	Value
WASTE ESTIMATION	Type	“Other”
	Effluent Vol per day (ADWF)	77 kL/day
	TN (mg/L)	11 for MBR/Activated Sludge; 35 for Biolytix.
	TP (mg/L)	2 for MBR/Activated Sludge; 8 for Biolytix.
	Operating Period	7 days/week
CLIMATE	Site Name	Moranbah
	Latitude	22° 00' S
	Longitude	148° 05' E
	Start Date	1/1/1957
	End Date	31/12/2005
SOIL TYPE		Clayey Sand ¹⁷
STORAGE		308 kL
PLANT		Kikuyu
IRRIGATION	Area Available	Variable – to be determined
	Trigger	Once every day
	Irrigate to:	5mm

¹⁷ From borehole data from adjacent site. ‘Clayey sand’ is not a standard profile in MEDLI, so an amalgam of the standard profiles of ‘Sand’ and “Grey Clay” were used.



Table 21 Summary of MEDLI Input Parameters – Temporary Accommodation with Composting Toilets

Category	Variable	Value
WASTE ESTIMATION	Type	“Other”
	Effluent Vol per day (ADWF)	77 kL/day
	TN (mg/L)	1923
	TP (mg/L)	2
	Operating Period	7 days/week
CLIMATE	Site Name	Moranbah
	Latitude	22° 00' S
	Longitude	148° 05' E
	Start Date	1/1/1957
	End Date	31/12/2005
SOIL TYPE		Clayey Sand ¹⁸
STORAGE		400 kL
PLANT		Kikuyu
IRRIGATION	Area Available	Variable – to be determined
	Trigger	Once every day
	Irrigate to:	1 - 5mm considered

¹⁸ From borehole data from adjacent site. ‘Clayey sand’ is not a standard profile in MEDLI, so an amalgum of the standard profiles of ‘Sand’ and “Grey Clay” were used.



GHD Pty Ltd ABN 39 008 488 373

201 Charlotte Street Brisbane Qld 4000



GPO Box 668 Brisbane Qld 4001 Australia

T: (07) 3316 3000 F: (07) 3316 3333 E: bnemail@ghd.com.au

© **GHD Pty Ltd 2006**

This document is and shall remain the property of GHD Pty Ltd. The document may only be used for the purposes for which it was commissioned and in accordance with the Terms of Engagement for the commission. Unauthorised use of this document in any form whatsoever is prohibited.

Document Status

Rev No.	Author	Reviewer		Approved for Issue		
		Name	Signature	Name	Signature	Date
1	C. Waterhouse and T. Kent	L. Gibson		L. Gibson		4/8/06